

Eaton rotary disconnect switch

R5A3025U

UPC:786685402864

Dimensions:

- **Height:** 3.35 IN
- **Length:** 2.57 IN
- **Width:** 1.77 IN

Weight:.5 LB

Notes:Suitable as motor disconnect

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Amperage Rating:** 25A
- **Fuse Configuration:** Non-fusible
- **Number Of Poles:** Three-pole
- **Product Category:** Rotary Switch
- **Series:** R5
- **Voltage Rating:** 600V

Supporting documents:

- [Pringle Switches - Bolted contact switches](#)
- [Eatons Volume 2-Commercial Distribution](#)
- [R5A30_U AutoCAD 2D Footprint](#)
- [R5A30_U 3D Inventor](#)
- [R5A30_U 3D Model Xchange](#)
- [R5A30_U 2D Drawing Xchange](#)
- [R5A30_U 2D PDF](#)
- [R5A30_U AutoCAD 2D Footprint \(mm\)](#)
- [Eaton Specification Sheet - R5A3025U](#)

Certifications:

- CSA Certified
- UL 508



- IEC Rated
- EN Listed

Product compliance:

- CCC Marked

© 2016 Eaton. All rights reserved.