

POWER INSTALLED SCREW ANCHORS

Hubbell offers a line of power installed screw anchors with a beveled leading edge. Beveled leading edge improves installation in hard and frozen soils. Installs with CHANCE® Anchor Installation tooling.



T1022021
Tough One* - 2.25" Hub



T1025060
Tough One* - 2.25" Hub



C199020103
Pisa* Solid Hub

CATALOG NUMBER	ANCHOR STYLE	HUB/SHAFT SIZE	TORQUE RATING	HELIX DIAMETER(S)	HELIX LEADING EDGE	THREAD SIZE	FITS ROD DIAMETER
T1022021	Tough One* Socket	2.25" (57.1 mm)	10,000 Ft Lbs (13,558 N-M)	8" (203 mm)	Beveled	1" (25.4 mm)	0.75" (19.1 mm) or 1" (25.4 mm)
T1022022	Tough One* Socket	2.25" (57.1 mm)	10,000 Ft Lbs (13,558 N-M)	10" (254 mm)	Beveled	1" (25.4 mm)	0.75" (19.1 mm) or 1" (25.4 mm)
T1022023	Tough One* Socket	2.25" (57.1 mm)	10,000 Ft Lbs (13,558 N-M)	12" (304 mm)	Beveled	1" (25.4 mm)	0.75" (19.1 mm) or 1" (25.4 mm)
T1022024	Tough One* Socket	2.25" (57.1 mm)	10,000 Ft Lbs (13,558 N-M)	14" (355 mm)	Beveled	1" (25.4 mm)	0.75" (19.1 mm) or 1" (25.4 mm)
T1025060	Tough One* Socket	2.50" (63.5 mm)	15,000 Ft Lbs (20,340 N-M)	8" (203 mm)	Beveled	1" (25.4 mm)	0.75" (19.1 mm) or 1" (25.4 mm)
T1025061	Tough One* Socket	2.50" (63.5 mm)	15,000 Ft Lbs (20,340 N-M)	10" (254 mm)	Beveled	1" (25.4 mm)	0.75" (19.1 mm) or 1" (25.4 mm)
T1025062	Tough One* Socket	2.50" (63.5 mm)	15,000 Ft Lbs (20,340 N-M)	12" (304 mm)	Beveled	1" (25.4 mm)	0.75" (19.1 mm) or 1" (25.4 mm)
T1025063	Tough One* Socket	2.50" (63.5 mm)	15,000 Ft Lbs (20,340 N-M)	14" (355 mm)	Beveled	1" (25.4 mm)	0.75" (19.1 mm) or 1" (25.4 mm)
C199020103	Solid Hub	1.37" (34.9 mm)	4,000 Ft Lbs (5,424 N-M)	8" (203 mm)	Beveled	1" (25.4 mm)	0.75" (19.1 mm) or 1" (25.4 mm)
C199020104	Solid Hub	1.37" (34.9 mm)	4,000 Ft Lbs (5,424 N-M)	10" (254 mm)	Beveled	1" (25.4 mm)	0.75" (19.1 mm) or 1" (25.4 mm)
C199020105	Solid Hub	1.37" (34.9 mm)	4,000 Ft Lbs (5,424 N-M)	12" (304 mm)	Beveled	1" (25.4 mm)	0.75" (19.1 mm) or 1" (25.4 mm)
C199020107	Solid Hub	1.37" (34.9 mm)	4,000 Ft Lbs (5,424 N-M)	Two 10" (254 mm)	Beveled	1" (25.4 mm)	0.75" (19.1 mm) or 1" (25.4 mm)
C199020109	Solid Hub	1.5" (38.1 mm)	6,000 Ft Lbs (8,136 N-M)	8" (203 mm)	Beveled	1" (25.4 mm)	0.75" (19.1 mm) or 1" (25.4 mm)
C199020110	Solid Hub	1.5" (38.1 mm)	6,000 Ft Lbs (8,136 N-M)	10" (254 mm)	Beveled	1" (25.4 mm)	0.75" (19.1 mm) or 1" (25.4 mm)
C199020111	Solid Hub	1.5" (38.1 mm)	6,000 Ft Lbs (8,136 N-M)	12" (304 mm)	Beveled	1" (25.4 mm)	0.75" (19.1 mm) or 1" (25.4 mm)
C199020112	Solid Hub	1.5" (38.1 mm)	6,000 Ft Lbs (8,136 N-M)	Two 8" (203 mm)	Beveled	1" (25.4 mm)	0.75" (19.1 mm) or 1" (25.4 mm)
C199020113	Solid Hub	1.5" (38.1 mm)	6,000 Ft Lbs (8,136 N-M)	Two 10" (254 mm)	Beveled	1" (25.4 mm)	0.75" (19.1 mm) or 1" (25.4 mm)
C199020114	Solid Hub	1.5" (38.1 mm)	7,000 Ft Lbs (9,492 N-M)	8" (203 mm)	Beveled	1" (25.4 mm)	0.75" (19.1 mm) or 1" (25.4 mm)
C199020116	Solid Hub	1.5" (38.1 mm)	7,000 Ft Lbs (9,492 N-M)	Two 8" (203 mm)	Beveled	1" (25.4 mm)	0.75" (19.1 mm) or 1" (25.4 mm)
C199020117	Solid Hub	1.5" (38.1 mm)	7,000 Ft Lbs (9,492 N-M)	Two 10" (254 mm)	Beveled	1" (25.4 mm)	0.75" (19.1 mm) or 1" (25.4 mm)

