

Universal Tool Accessories

----- See Universal Tool KITS on Page 2119 -----




Pin Holder

For replacing pins and bolts. Bolt head fits into a slot and is held tight by spring action. Will take bolts or pins up to 5/8" diameter. Fits EEI and NEMA insulators. Part No. M44552.....10 oz.



Key Remover

Hammer-like action makes it extremely useful in pulling out stuck cotter keys. Release of the compression spring by a



quick jerk of the pole deals the cotter key a hammer blow without disengaging the eye. Part No. M445512.....8 oz.



3

S

Q

1

Π

Q

I Q 5

0

0

0

S

I

N

Cutout Tool

While this tool was designed for removing and replacing the doors of enclosed cutouts, its finger-like grasp makes it useful on many other jobs where a sure grip is required. Jaws open to accommodate an object 3-3/4 " wide. All parts that contact porcelain are plastisol covered. Part No. M44555.....1³/₄ lb.

Locating Pin

Folding Rule

congested areas.

Adaptable to many uses.

obtaining measurements

Part No. M445516....81/2 oz.

near live conductors in

Particularly suited for

Used as a drift pin in aligning bolt holes as an aid in bolt and pin insertions. Recommended for making hardware connections on tower transmission lines and line deadends where aligning or hardware fitting is difficult. Part No. M445515..... 10 oz.







Ratchet Wrench

¹/₂"-square drive

This Ratchet Wrench is used for tightening bolts in substation equipment, hardware, transmission and distribution lines, etc. Part No. M4455.....1³/₄ lb.

Disconnect

Used for opening and closing switches, opening enclosed cutouts, etc. Aluminum: Part No. M44559......2 oz. Bronze[.] Part No. C4001418.....6 oz.



Chuck Blank (5/8" opening)

Screw drivers, hack saws, and other tools may be inserted in this device and secured by soldering. For wingnut tightened Chuck Blank order No. M445537.

Part No. M445510...... 4¹/₂ oz.

Fixed Prong Tie Stick Head

Often preferred for manipulating tie wires which have looped ends. Useful in close quarters where loose ends of tie wire must be rolled up to prevent contact with crossarm or hardware while untying.

Part No. M445517.....1 lb.

Chuck Blank (5/8" opening)

The Chuck Blank can be used for a variety of applications, such as inserting screw drivers, saws, etc. The wing nut tightens the installed tool.

Part No. M445537..... 5 oz.



