



PAR LAMPS : PAR 20, 30, 30S, 38

DESCRIPTION

LED PAR Replacement Lamps directly replace incandescent PAR lamps at a fraction of the energy cost.

FEATURES

- Compatible with a wide array of dimmers
- +25,000 hour rated life for ENERGY STAR® Approved lamps*
- 50,000 hour design life**
- Up to 80% electricity savings vs. halogen
- No mercury or UV/IR emissions
- Shatter-resistant for reduced risk of injury and breakage

WARRANTY

- 5 year limited warranty; see eiko.com for warranty details

APPLICATIONS

- Recessed / Track Lighting
- Property Management
- Accent / Display Lighting
- Retail / Residential
- Hospitality
- Houses of Worship
- Healthcare
- Task Lighting



* Early initial qualification for ENERGY STAR allows for directional lamp life claims of 25,000 hours (L70) with 3,000 hour actual test data, LM80 data and in-situ temperature measurements. As the lamps pass ENERGY STAR requirements, manufacturers may increase the lifetime of a product as dictated by ENERGY STAR guidelines. See http://www.energystar.gov/index.cfm?fuseaction=products_for_partners.showLightbulbs for further details.

** Design life is based on engineering testing and probability analysis



| | | | | | |
|---------------------|-----------------------|--|-----|-------|-------|
| PERFORMANCE | Power Consumption | 7W | 11W | 13W | 15W |
| | Lumens | 500 | 850 | 1,050 | 1,250 |
| | Efficacy (LPW) | 71 | 77 | 81 | 83 |
| | CRI | 80+ | | | |
| | Beam | 30°, 40° | | | |
| | CCT | 2700K, 3000K, 4000K, 5000K | | | |
| | Life (L70) | 25,000 hours* | | | |
| ELECTRICAL | Power Factor | >0.7 | | | |
| | THD | <20% | | | |
| | Input Voltage | 120V | | | |
| CONSTRUCTION | Operating Temperature | -40°F to 104°F (-40°C to 40°C) | | | |
| | Base | E26 | | | |
| LISTINGS | Certification(s) | ENERGY STAR® Rated; cULus Classified | | | |
| | Material Usage | RoHS Compliant; no mercury or lead | | | |
| | Environment | Wet or Damp location rated; not for use in enclosed fixtures, with electronic timers, photo-cells, or motion/occupancy sensors | | | |

PERFORMANCE SUMMARY

| Order Code | Item # | Lumens | Watts | CCT | CRI | Beam | MOL | MOD | Life/Hours | Replaces Incan. | Damp Location Rated | Wet Location Rated | ES |
|------------|-----------------------------|--------|-------|-------|-----|------|-------|-------|------------|-----------------|---------------------|--------------------|----|
| 10782 | LED7WPAR20/FL/827-DIM-G9 | 500 | 7W | 2700K | 80+ | 40° | 3.19" | 2.48" | 25,000 | 50W | | | ★ |
| 10783 | LED7WPAR20/FL/830-DIM-G9 | 500 | 7W | 3000K | 80+ | 40° | 3.19" | 2.48" | 25,000 | 50W | | | ★ |
| 10784 | LED7WPAR20/FL/840-DIM-G9 | 500 | 7W | 4000K | 80+ | 40° | 3.19" | 2.48" | 25,000 | 50W | | | ★ |
| 10785 | LED7WPAR20/NFL/827-DIM-G9 | 500 | 7W | 2700K | 80+ | 30° | 3.19" | 2.48" | 25,000 | 50W | | | ★ |
| 10786 | LED7WPAR20/NFL/830-DIM-G9 | 500 | 7W | 3000K | 80+ | 30° | 3.19" | 2.48" | 25,000 | 50W | | | ★ |
| 10787 | LED7WPAR20/NFL/840-DIM-G9 | 500 | 7W | 4000K | 80+ | 30° | 3.19" | 2.48" | 25,000 | 50W | | | ★ |
| 10766 | LED11WPAR30/FL/827-DIM-G9 | 850 | 11W | 2700K | 80+ | 40° | 4.53" | 3.74" | 25,000 | 75W | | | ★ |
| 10767 | LED11WPAR30/FL/830-DIM-G9 | 850 | 11W | 3000K | 80+ | 40° | 4.53" | 3.74" | 25,000 | 75W | | | ★ |
| 10768 | LED11WPAR30/FL/840-DIM-G9 | 850 | 11W | 4000K | 80+ | 40° | 4.53" | 3.74" | 25,000 | 75W | | | ★ |
| 10769 | LED11WPAR30/FL/850-DIM-G9 | 850 | 11W | 5000K | 80+ | 40° | 4.53" | 3.74" | 25,000 | 75W | | | ★ |
| 10770 | LED11WPAR30/NFL/827-DIM-G9 | 850 | 11W | 2700K | 80+ | 30° | 4.53" | 3.74" | 25,000 | 75W | | | ★ |
| 10771 | LED11WPAR30/NFL/830-DIM-G9 | 850 | 11W | 3000K | 80+ | 30° | 4.53" | 3.74" | 25,000 | 75W | | | ★ |
| 10772 | LED11WPAR30/NFL/840-DIM-G9 | 850 | 11W | 4000K | 80+ | 30° | 4.53" | 3.74" | 25,000 | 75W | | | ★ |
| 10773 | LED11WPAR30S/FL/827-DIM-G9 | 850 | 11W | 2700K | 80+ | 40° | 3.62" | 3.74" | 25,000 | 75W | | | ★ |
| 10774 | LED11WPAR30S/FL/830-DIM-G9 | 850 | 11W | 3000K | 80+ | 40° | 3.62" | 3.74" | 25,000 | 75W | | | ★ |
| 10775 | LED11WPAR30S/FL/840-DIM-G9 | 850 | 11W | 4000K | 80+ | 40° | 3.62" | 3.74" | 25,000 | 75W | | | ★ |
| 10776 | LED11WPAR30S/NFL/827-DIM-G9 | 850 | 11W | 2700K | 80+ | 30° | 3.62" | 3.74" | 25,000 | 75W | | | ★ |
| 10777 | LED11WPAR30S/NFL/830-DIM-G9 | 850 | 11W | 3000K | 80+ | 30° | 3.62" | 3.74" | 25,000 | 75W | | | ★ |
| 10788 | LED13WPAR38/FL/827-DIM-G9 | 1,050 | 13W | 2700K | 80+ | 40° | 5.12" | 4.72" | 25,000 | 120W | 💧 | | ★ |
| 10789 | LED13WPAR38/FL/830-DIM-G9 | 1,050 | 13W | 3000K | 80+ | 40° | 5.12" | 4.72" | 25,000 | 120W | 💧 | | ★ |
| 10790 | LED13WPAR38/FL/840-DIM-G9 | 1,050 | 13W | 4000K | 80+ | 40° | 5.12" | 4.72" | 25,000 | 120W | 💧 | | ★ |
| 10778 | LED15WPAR38/FL/827-DIM-G9 | 1,250 | 15W | 2700K | 80+ | 40° | 5.12" | 4.72" | 25,000 | 150W | 💧 | | ★ |
| 10779 | LED15WPAR38/FL/830-DIM-G9 | 1,250 | 15W | 3000K | 80+ | 40° | 5.12" | 4.72" | 25,000 | 150W | 💧 | | ★ |
| 10780 | LED15WPAR38/FL/840-DIM-G9 | 1,250 | 15W | 4000K | 80+ | 40° | 5.12" | 4.72" | 25,000 | 150W | 💧 | | ★ |
| 10781 | LED15WPAR38/FL/850-DIM-G9 | 1,250 | 15W | 5000K | 80+ | 40° | 5.12" | 4.72" | 25,000 | 150W | 💧 | | ★ |
| 10069 | LED15WPAR38/FL/827-DIM-G8 | 1,250 | 15W | 2700K | 80+ | 40° | 5.16" | 4.72" | 25,000 | 120W | | 💧 | ★ |
| 09990 | LED15WPAR38/FL/830-DIM-G8 | 1,250 | 15W | 3000K | 80+ | 40° | 5.16" | 4.72" | 25,000 | 120W | | 💧 | ★ |
| 09991 | LED15WPAR38/FL/840-DIM-G8 | 1,250 | 15W | 4000K | 80+ | 40° | 5.16" | 4.72" | 25,000 | 120W | | 💧 | ★ |
| 09992 | LED15WPAR38/FL/850-DIM-G8 | 1,250 | 15W | 5000K | 80+ | 40° | 5.16" | 4.72" | 25,000 | 120W | | 💧 | ★ |

NOTE: Use order code when ordering. 💧Wet Location Rated ★ENERGY STAR® Approved

DIMENSIONS

