

With the same advantages as regular LED T8 lamps, Safety coated lamps are shatterproof to protect employees, production, customers and your business reputation.

- ▶ PTFE coated lamps will contain glass if a lamp is broken.
- ▶ All lamps are NSF rated for food equipment safety.
- ▶ This is the perfect solution for commercial kitchens, art galleries, museums and schools.

Safety Max T8 - S3



Order code	Description	Base	Average System Watts			Initial lumens ¹			Colour temp. (K)	CRI	Average life L70 (hrs)	Dimmable ² (Y/N)	Case qty
			(W)			(lm)							
			LBF	NBF	HBF ³	LBF	NBF	HBF					
T8 2 ft													
Length: 24 in. (610 mm)													
64815 ⁴	LED/T8/S3/9W/830/24/STD/SMX	G13	10	12	16	1 000	1 200	1 600	3 000	83	50 000	N	25
64816 ⁴	LED/T8/S3/9W/835/24/STD/SMX	G13	10	12	16	1 000	1 200	1 600	3 500	83	50 000	N	25
64832	LED/T8/S3/9W/840/24/STD/SMX	G13	10	12	16	1 000	1 200	1 600	4 000	83	50 000	N	25
T8 3 ft													
Length: 36 in. (915 mm)													
64817 ⁴	LED/T8/S3/13W/830/36/STD/SMX	G13	15	16	20	1 500	1 600	2 000	3 000	83	50 000	N	25
64818 ⁴	LED/T8/S3/13W/835/36/STD/SMX	G13	15	16	20	1 500	1 600	2 000	3 500	83	50 000	N	25
64833 ⁴	LED/T8/S3/13W/840/36/STD/SMX	G13	15	16	20	1 500	1 600	2 000	4 000	83	50 000	N	25
T8 4 ft													
Length: 48 in. (1 220 mm)													
64837	LED/T8/S3/18W/830/48/STD/SMX	G13	17	22	30	1 700	2 250	3 000	3 000	83	50 000	N	25
64838	LED/T8/S3/18W/835/48/STD/SMX	G13	17	22	30	1 700	2 250	3 000	3 500	83	50 000	N	25
64820	LED/T8/S3/18W/840/48/STD/SMX	G13	17	22	30	1 750	2 300	3 050	4 000	83	50 000	N	25
64821	LED/T8/S3/18W/850/48/STD/SMX	G13	17	22	30	1 800	2 400	3 100	5 000	83	50 000	N	25



Intertek
CONFORMS TO NSF/ANSI 2



¹ Typical lumens +/- 10 %

² For a complete list of compatible dimmers and DLC qualified products, please visit www.standardpro.com

³ LBF= Low ballast factor, NBF= Neutral ballast factor, HBF= High ballast factor

⁴ Not DLC

Fluorescent Replacements