

CHANCE[®]

Insulated Hand Tools



Catalog 2100 March 2020

Insulated Hand Tools -2100



Grip-All Clampsticks External Control Rod

- External Operating Rod Type
- Tested per OSHA & ASTM F711
- Versatile tool puts an easy-to-control “finger” on an insulated pole
- Primarily designed for installing hot-line and grounding clamps
- Also serves both overhead and underground circuits with various end fittings

Operation

- Operating mechanism (or “shotgun”) incorporates a sliding hand grip that opens the hook to grasp a clamp eyescrew and retract it into tool head
- Latch must be depressed to release locked hand grip that opens the hook
- For smooth operation, investment-cast stainless-steel components include Jaw, Jaw Holder, Safety Stop, Lockbar and Latch illustrated below
- Lexan® tool head is designed for close-quarter operations
- Worker must maintain recommended work distance based solely on the Epoxiglas® pole section of the handle, as the hook and its actuator are metal parts
- Easy-care Grip-All Clampsticks do not require field stripping to clean
- All insulated parts, including the operating rod, are outside the main pole, readily accessible to wipe dry



To accept grounding clamps with long eyescrews, all Grip-All clampsticks feature 6¾ inches of head travel.

Notch in tool head aligns the clamp while the operator places it.

Single-Piece Style

†Catalog No.	Overall Length	Weight	*Storage Bag
C4030291	1¼" x 4' 9"	5¾ lb./2.6 kg.	P6434
C4030292	1¼" x 6' 8"	6½ lb./2.9 kg.	P6436
C4030293	1¼" x 8' 7"	7¼ lb./3.3 kg.	P6438
C4030294	1¼" x 10' 7"	8 lb./3.6 kg.	P64310
C4030295	1¼" x 12' 7"	8¾ lb./3.9 kg.	P64312

†For metal universal fitting, add suffix "A".

*For storage bags, see Catalog Section 2500.

Hinged Style

Ideal for troubleshooters with limited tool-storage space in their vehicles, this folding version operates with the same features as the one-piece style.

†Catalog No.	Folded	Extended	Weight	*Storage Bag
C4030296	3'4"	1¼" x 6' 9"	8 lb./3.6 kg.	P6432
C4030297	4'4"	1¼" x 8' 8"	9 lb./4.1 kg.	P6432
C4030298	5'4"	1¼" x 10' 8"	10 lb./4.5 kg.	P6433
C4030299	6'4"	1¼" x 12' 8"	10½ lb./4.7 kg.	P6435
C4030342	7'4"	1¼" x 14' 8"	11 lb./5.0 kg.	PSP6435005
C4030343	8'4"	1¼" x 16' 8"	11½ lb./5.2 kg.	PSP6435004

†For metal universal fitting, add suffix "A".

*For storage bags, see Catalog Section 2500.

†For metal universal fitting on handle end of any Single-Piece or Hinged Grip-All, add suffix "A" to the Catalog Number.



To convert any Grip-All stick to use all Universal Tool Accessories, the M1867 Adapter secures in the clampstick hook and head housing.



*fits Chance Grip-all only

M1867

Replacement Parts for External Control Single-Piece and Hinged Grip-All Clampsticks

Head Repair Kit, also available as Cat. No. C4031420, includes head, roll pin, epoxy bond kit and instructions.

