REPLACES UP TO 400W HID

150W Flood / Area Light



Ideal for outdoor applications such as parking lots, construction sites, storage and rail yards, industrial locations, marinas, billboard/sign illumination and more



Optional Field-Interchangable Mounting Arms (ordered separately)



Slip Fit FL01P-SF



Horizontal Arm FL01P-HA



Round Pole FL01P-RPA

TECHNICAL DATA






LIGHT SPECIFICATIONS

Lumens	20,680
Efficacy	138.23 lm/W
CCT	5000K
Beam angle	90 x 120°
CRI	70
Dimmable	0-10V
Rated hours	50,000
Warranty	10-year


APPROVALS AND LISTINGS

cUL	E482965
DLC	PLD0G6TQ97LE

ILLUMINANCE AT A DISTANCE



ISOCANDELA PLOT




ELECTRICAL

Wattage	150W
Voltage	120-277V
Power factor	0.90
THD	15%
Operating temp	-40° to 40°C

CONSTRUCTION

Housing	Aluminum
Finish	6mm, powder-coat
Colour	Bronze
IP rating	IP65
Weight	13.6 lbs
Carton qty	1

DIMENSIONS



Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | ordersbc@csc-led.com

