

313/315 Series Lead-Free 3AG, Slo-Blo® Fuse



Description

The 3AG Slo-Blo® fuse solves a broad range of application requirements while offering reliable performance and cost-effective circuit protection.

The fuse catalog number with the suffix "ID" instantly identifies itself upon opening by showing a discoloration of its glass body. Guesswork and time consuming circuit testing are eliminated. This unique design offers the same quality performance characteristics as the standard 3AG Slo-Blo® Fuse design.

Agency Approvals

Agency	Agency File Number	Ampere Range
	E10480	0.010A - 10A**
	29862	0.010A - 10A**/15A**
	E10480	10A - 30A
	313 Series (Cartridge): NBK060618-E10480A NBK060618-E10480C	1-5A 6.25- 10A**
	315 Series (Leaded): NBK060618-E10480B NBK060618-E10480D	1-5A 6.25-10A**
	SU05001-6004	2.25-2.5A
	SU05001-5007	2.8A - 3.2A
	SU05001-5008	4A - 6.3A
	SU05001-5009	7A-8A
	N/A	0.010A - 10A**/15A**

** See note under Electrical Characteristics by item

Features

- In accordance with UL Standard 248-14
- Available in cartridge and axial lead format and with various forming dimensions
- RoHS compliant and Lead-free

Applications

Used as supplementary protection in appliance or utilization equipment to provide individual protection for components or internal circuits.

Additional Information



**Datasheet
313 Series**



**Resources
313 Series**



**Samples
313 Series**



**Accessories
313 & 315 Series**



**Datasheet
315 Series**



**Resources
315 Series**



**Samples
315 Series**

For recommended fuse accessories for this product series, see '[Recommended Accessories](#)' section.

Electrical Characteristics by Series

% of Ampere Rating	Ampere Rating	Opening Time
100%	10mA – 30A	4 hours, Minimum
135%	10mA – 30A	1 hour, Maximum
200%	10mA – 15A	5 sec., Min., 30 sec., Max
	20A – 30A	5 sec., Min., 60 sec Max

Electrical Characteristic Specifications by Item

Amp Code	Ampere Rating (A)	Voltage Rating (V)	Interrupting Rating	Nominal Cold Resistance (Ohms)	Nominal Melting P _t (A ² sec)	Agency Approvals					
						UL	SR	CCC	RU	PS E	CE
0.01	0.01	250	35A@250Vac 10KA@125Vac	4300.0000	0.000121	x	x				x
0.031	0.031	250		430.0000	0.00303	x	x				x
0.04	0.04	250		300.0000	0.00630	x	x				x
0.062	0.062	250		120.0000	0.0210	x	x				x
0.1	0.1	250		43.0000	0.0850	x	x				x
0.125	0.125	250		30.0000	0.152	x	x				x
0.15	0.15	250		20.0000	0.270	x	x				x
0.175	0.175	250		8.6700	0.177	x	x				x
0.187	0.187	250		8.0100	0.230	x	x				x
0.2	0.2	250		6.5900	0.270	x	x				x
0.25	0.25	250		4.2700	0.385	x	x				x
0.3	0.3	250		3.1350	0.730	x	x				x
0.375	0.375	250		2.0950	1.23	x	x				x
0.4	0.4	250		1.8750	1.35	x	x				x
0.5*	0.5	250		1.2600	2.55	x	x				x
0.6	0.6	250		0.9120	4.00	x	x				x
0.7	0.7	250		0.7000	5.90	x	x				x
0.75	0.75	250		0.6215	7.16	x	x				x
0.8	0.8	250		0.5540	8.00	x	x				x
1.0*	1	250		0.3750	14.0	x	x			x	x
1.2	1.2	250		0.2780	21.5	x	x			x	x
1.25	1.25	250		0.2600	24.0	x	x			x	x
1.5*	1.5	250		0.1910	38.0	x	x			x	x
1.6	1.6	250		0.1710	49.6	x	x			x	x
1.8	1.8	250		0.1410	92.0	x	x			x	x
2.0*	2	250	0.1169	77.0	x	x			x	x	
2.25	2.25	250	0.0968	121	x	x	x		x	x	
2.5	2.5	250	0.0811	199	x	x	x		x	x	
2.8	2.8	250	0.0675	269	x	x	x		x	x	
3.*	3	250	0.0593	200	x	x	x		x	x	
3.2	3.2	250	0.0529	209	x	x	x		x	x	
4.0*	4	250	0.0311	76.1	x	x	x		x	x	
5.0*	5	250	0.0214	276	x	x	x		x	x	
6.25*	6.25	250	0.0154	388	x	x	x		x	x	
6.3	6.3	250	0.0154	388	x	x	x		x	x	
7.0*	7	250	0.0128	547	x	x	x		x	x	
8.0*	8	250	0.0111	701	x	x	x		x	x	
10.0**	10	250	0.0083	1285	x	x			x	x	
10.0*	10	32	0.0083	1285				x			
12.0	12	32	0.0065	1200				x			
15.0**	15	125	0.0050	2650		x		x	x	x	
15.0	15	32	0.0050	2650				x			
20.0	20	32	0.0022	9560				x			
25.0	25	32	0.0017	16500				x			
30.0	30	32	0.0012	26900				x			

* For 313series, these ratings available with an indicating option. Add the "ID" designation to the series number. i.e. 313.500ID.


** The 10A and 15A ratings are ratings are designed for special voltage requirement. For 10A, it is available as 250Vac rated and the part number is 0313010.MX250P; For 15A, it is available as 125Vac rated and the part number is 0315015.MX125P.

Product Characteristics

Materials	Body: Glass Cap: Nickel-plated brass Leads: Tin-plated Copper
Terminal Strength	MIL-STD-202, Method 211, Test Condition A
Solderability	MIL-STD-202 method 208
Product Marking	Cap1: Brand logo, current and voltage ratings Cap2: Series and agency approval marks


Operating Temperature	-55°C to +125°C
Thermal Shock	MIL-STD-202, Method 107, Test Condition B: (5 cycles -65°C to +125°C)
Vibration	MIL-STD-202, Method 201
Humidity	MIL-STD-202, Method 103, Test Condition A: High RH (95%) and Elevated temperature (40°C) for 240 hours
Salt Spray	MIL-STD-202, Method 101, Test Condition B

Dimensions



Measurements displayed in millimeters (inches)

Part Numbering System



Recommended Accessories

Accessory Type	Series	Description	Max Application Voltage	Max Application Amperage
Holder	155100	Twist-Lock In-Line Fuseholder	32	20
	342	Traditional Panel Mount Fuseholder	250	20
	346	Panel Mount Flip-Top Shock-Safe Fuseholder	250	15
	345	Shock-Safe Fuseholder with PC Mount, Solder Mount and Panel Mount options	250	16
Block	354	Low Profile OMNI-BLOK® Fuse Block	600	30
	359	High Current Screw Terminal Fuse Block		30
Clip	122	High Current Traditional PC Board Fuse Clip	1000	30
	101	Rivet/Eyelet Type Fuse Clip	1000	15

Notes:

- Do not use in applications above rating.
- Please refer to fuseholder data sheet for specific re-rating information.
- Please contact factory for applications greater than the max voltage and amperage shown.