

40W

ROTATABLE LUMINAIRE



Ideal for security lighting, wall washing, flood lighting, and more  
Use as an uplight, downlight, or flood light

Rotatable  
to offer flexible light control

Oversized Heat Sink  
for superior thermal  
management



Heavy Die Cast  
Aluminum

Superior  
anodized  
paint finish



LM80 tested  
CREE chips

Optional Extension Plate: RWP-EXT-PLATE  
(ordered separately)

## TECHNICAL DATA



### LIGHT SPECIFICATIONS

|             |             |
|-------------|-------------|
| Lumens      | 5,238.3 lm  |
| Efficacy    | 126.19 lm/W |
| CCT         | 4000K       |
| Beam angle  | 60°         |
| CRI         | 73.5        |
| Dimmable    | No          |
| Rated hours | 50,000      |
| Warranty    | 10-year     |

### APPROVALS AND LISTINGS

|             |              |
|-------------|--------------|
| cUL         | E482965      |
| DLC PREMIUM | PLPTVLD73PR7 |

### DIMENSIONS



MAKE THE SMART CHOICE.  
 COMPARE LUMENS PER WATT  
**126+ LM/W**

### ELECTRICAL

|                |               |
|----------------|---------------|
| Wattage        | 40W           |
| Voltage        | 100-277V      |
| Power factor   | 0.9           |
| THD            | 18.95%        |
| Operating temp | -30° to 45° C |

### CONSTRUCTION

|            |                 |
|------------|-----------------|
| Housing    | Cast aluminum   |
| Finish     | Anodized finish |
| Colour     | Black           |
| IP rating  | IP65            |
| Weight     | 4.29 lbs        |
| Carton qty | 4               |

### ILLUMINANCE CONE

