Power devices



Heavy duty grade power receptacles

Product description

2-pole, 3-wire grounding 30A, 125V/AC 30A, 250V/AC







5-30R 6-30R TT-30R



1263



Design features

- Heavy gauge galvanized steel mounting strap for corrosion resistance
- For use with copper or aluminum wire
- Flush receptacles fit one-gang or two-gang enclosures
- Surface receptacles have patented lay-in terminals that accept up to #4 AWG wire
- Surface receptacle backs feature concentric knockouts and an adjustable cord clamp to allow wiring from back or bottom

Flush power receptacles





Rating						Æ ⚠
Α	V/AC	NEMA	Description	Color	Catalog no.	
30	125	TT-30R	Flush mount power receptacle, matching plug 83	BK	□ 1263	• •
Liste	ed to UL49	98, file no. E	15058; CSA certified to CSA C22.2, no. 42			

Flush power receptacles







Rating						A
A	V/AC	NEMA	Description	Color	Catalog no.	♣ €
30	125	5-30R	Flush mount power receptacle, matching plug S41	BK	□1233	• •
30	250	6-30R	Flush mount power receptacle, matching plug S42	BK	□ 1234	• •
Liste	ed to UL49	98, file no. I	E15058; CSA certified to C22.2, no. 42; NOM certified			

Surface power receptacle





Rating						
Α	V/AC	NEMA	Description	Color	Catalog no.	RoHS)
30	250	6-30R	Surface mount power receptacle, matching plug S42	ВК	□ 1232	• •

Listed to UL498, file no. E15058; CSA certified to C22.2, no. 42; NOM certified

Panel power receptacles





A A	V/AC	NEMA	Description	Color	Catalog no.	ERAHS
30	125	TT-30R	Panel mount power receptacle, matching plug 83	BK	□ U1263	• •

Listed to UL498, file no. E15058; CSA certified to C22.2, no. 42; NOM certified

Color ordering information:

BK (Black)



Dimensional information: B-70 Specification information: Please visit www.eaton.com/wiringdevices Compliances, specifications and availability are subject to change without notice.



Indicates NAFTA compliant - Page G-21

