

CORDLESS CIRCULAR SAW BLADES

	Diameter	Arbor	Teeth	Application	Tooth Grind	Kerf	Max. RPM	For Models	Part No.
Cordless	7-1/4"	5/8" 16 mm	24 CT	Ripping, crosscutting and mitre cuts in hard and soft wood	M-Force (Micro-Polished)	0.076"	8,300 RPM	DHS711	A-94839-10
			24 CT	Ripping, crosscutting and mitre cuts in hard and soft wood, wet and pressure-treated lumber	M-Force (Ultra-Coated)				A-94530-10
			44 CT	Laminate, MDF, Melamine, Wood	MATAFR	0.057"	8,040 RPM		A-98784
			44 CT	Wood					A-98790
Benchtop	6-1/2"	5/8" 16 mm	16 CT	Framing - Fast Ripping	ATB	0.059"	4,770 RPM	DSS610 DSS611	T-01395
			24 CT	General Purpose Cutting - Ripping, Crosscutting, Mitre Cuts					A-85092
			24 CT	General Purpose Cutting - Ripping, Crosscutting, Mitre Cuts					T-01404
			40 CT	Finish Cutting - Crosscutting, Mitre Cuts					T-01410
			16 CT & 24 CT Combo		T-01426				
			44 CT	Laminate, MDF, Melamine, Wood	MATAFR	0.057"	A-93854		
			44 CT	Wood			A-93860		
Saws	5-7/8" NEW!	5/8" 16 mm	32 CT	Steel, Ferrous Metals	MTCG	0.059"	4,680 RPM	DCS551	A-96095
			52 CT	Thin Gauge Steel, Ferrous Metals	ATB	0.055"			A-96104
			52 CT	Aluminum, Non-Ferrous Metals	-	0.063"			A-96126
			60 CT	Stainless Steel (Max. 16 ga.)	Cermet	0.043"			A-96110
Woodworking	5-3/8"	5/8" 16 mm	16 CT	General Purpose Cutting in Hard & Soft Wood	ATAF	0.059"	4,500 RPM	DSS501	A-94904
			30 CT	Steel Pipe, Angle Iron, Channel	MTCG				A-95037
			50 CT	Thin Metal, Sheet Metal, Steel Studs, Mild Steel	ATB	DCS550		A-94524	
			50 CT	Aluminum	ATB			0.062"	A-95940
Hammers	3-3/8"	5/8" 16 mm	20 CT	Ripping Hard & Soft Wood	ATB	-	2,240 RPM	HS301D, SH01	A-95021
		9/16" 15 mm	Diamond Grit	Glass & Tile (Wet cutting only)	Continuous Rim	-	4,500 RPM	CC01, CC301D	A-95722

DRYWALL CUTTER BLADES



Part No.	Blade Length	Blade Width	Blade Thickness	Blade Material	Qty / Pk	Material / Thickness	For Model
B-49703	2-3/32"	3/4"	1/64"	HCS	2 / Pk	Drywall < 1-3/16"	DSD180
B-49719	2-5/32"					Wood < 1-3/16"	

13 IN 1 RATCHETING SCREWDRIVER

P-90386



Description	Includes
<ul style="list-style-type: none"> 3 position high torque ratchet (Forward – Lock – Reverse) 1/4" one touch quick release chuck can be removed for use in standard 3/8" or 1/2" Drill Chucks Bits store conveniently inside handle for quick and easy access Features textured ergonomic rubber grip 	<ul style="list-style-type: none"> 3 ea 1" Driver Bits S2, PH2 2" Driver Bits S1, S2, S3, PH1, PH2, PH3 2-1/4" Magnetic Bit Holder

18 IN 1 SCREWDRIVER

B-40571-6



Description	Includes
<ul style="list-style-type: none"> Stubby design ideal for use in restricted spaces 1/4" one touch quick release chuck can be removed for use in standard 3/8" or 1/2" drill chucks Bits conveniently store inside handle for quick and easy access 	<ul style="list-style-type: none"> 1" Driver Bits SQ1, SQ2 (x2), SQ3, PH1, PH2 (x2), PH3 2" Driver Bits SQ1, SQ2 (x3), SQ3, PH1, PH2 (x2), PH3 2-1/4" Magnetic Bit Holder

LASER DISTANCE MEASURERS

- Accuracy & Consistency
- Speed
- Versatility & Simplicity



NEW!

	LD030P	LD050P	LD080PI
Accuracy	5/64"	5/64"	1/64"
Operating Range	98'	164'	262'
Laser Class	II (<1 mW) @ 635 nm		
Power Supply	Two AAA Batteries		
Battery Life	Up to 5,000 Measurements	Up to 3,000 Measurements	Up to 5,000 Measurements
Measuring Units	4	6	7
Auto Power / Laser Off	Yes		
Adapts to Tripod	No	No	Yes
Reference Points	2	2	5
Continuous	Yes	No	Yes
Stake-Out	No	No	Yes
Distance	Yes		
Tilt	No	No	Yes
Area	Yes		
Volume	No	Yes	Yes
Minimum / Maximum	No	Yes	Yes
Add / Subtract	No	Yes	Yes
Pythagoras (Partial / 2 / 3)	No	No / Yes / Yes	Yes / Yes / Yes
Smart Horizontal	No	No	Yes
Height Tracking	No	No	Yes
Levelling	No	No	Yes
Timer	No	No	Yes
Memory	No	Last 5 Measurements	Last 20 Measurements