

Portable Band Saw 2107F



Large 4-314" x 4-314" Capadity with Excellent Tool Balance.

Increased Rigidity

Bridge construction of Aluminum frame and Motor housing makes the machine more durable.



Built-in Fluorescent Job Light

For clear view of ink line even in dark places. Switch for Fluorescent Job Light is independent of main switch.

Preset Dial for Speed Adjustment

Enables you to obtain suitable strokes per minutes for each cutting material.

Adjustable Stopper Plate

Retractable when cutting pipes near the wall or the floor, increasing maneuverability.



the set

PECIFICATIONS

	Continuous rating Input	710 W	
	Capacity	Round workpiece	
		: 120 mm (4-3/4") dia	
		Rectangular workpiece without stand	
		: 120 mm x 120 mm (4-3/4" x 4-3/4")	
	Blade speed	60 m (200 ft.) / min 105 m (350 ft.) / min.	
	Overall length	508 mm (20")	
	Net weight	5.7 kg (12.6 lbs)	
1	Power supply cord	2.5 m (8.2 ft.)	
	S	pecifications may differ from country to country.	

TANDARD EQUIPMENT

	Part No.
Carbon steel band saw blade (18 teeth per inch) 1 pc	*792559-8
Hex. wrench	783202-0

Items of standard equipment may differ from country to country. * 3pcs/set part No.

Band saw blade Width : 13 mm Thickness : 0.5 mm Length : 1,140 mm				
Kind of blade	Thickness of work-piece to be cut	No. of teeth per inch	Application	Part No.
		6	Wood	792567-9
Carbon	More than 5 mm	14	Plastics non-ferrous metal Mild steel, cast steel cast iron	792560-3
steel (3pcs./set)	4 mm-5 mm	18		792559-8
() [· · · · · · · · ·	Less than 4 mm	24		792558-0
Highspeed	4 mm-5 mm	14	Plastics, non-ferrous metal Mild steel, cast steel cast iron, Hard steel stainless steel	792557-2
steel	More than 5 mm	18		792556-4
(1pc./set)	Less than 4 mm	24		792555-6



Makita Corporation

3-11-8, Sumiyoshi-cho, Anjo, Aichi 446-8502, Japan PRINTED IN JAPAN Z23145-2 2004-9