

Accessories
TS 35X7.5/LL/6 2M/ST/ZN**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com**Product image**

Similar to illustration

General ordering data

Type	TS 35X7.5/LL/6 2M/ST/ZN
Order No.	0514570000
Version	Rail, TS 35, TS 35 x 7.5, with slot, Steel, galvanic zinc plated and passivated
GTIN (EAN)	4008 190980009
Qty.	2 m

Creation date September 2, 2020 7:06:46 AM CEST

Catalogue status 28.08.2020 / We reserve the right to make technical changes.

Accessories TS 35X7.5/LL/6 2M/ST/ZN

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Width	35 mm	Width (inches)	1.378 inch
Height	35 mm	Height (inches)	1.378 inch
Depth	7.5 mm	Depth (inches)	0.295 inch
Net weight	155 g		

Mounting rail

Drill-hole diameter	5.2 mm	Short circuit strength corresponds to E-Cu wire	16 mm ²
Short-time withstand current according to IEC 60947-7-2	1.92 kA/1s	Slit gap	7 mm
Slit length	18 mm	Slit width	6.2 mm
Slotted drill holes	Yes	Solder eyelet hole diameter (D)	5.2 mm
Spacing of holes, centre-to-centre	25 mm	Thickness	1 mm

Classifications

ETIM 6.0	EC001285	ETIM 7.0	EC001285
eClass 9.0	27-40-06-02	eClass 9.1	27-40-06-02
eClass 10.0	27-40-06-02		

Approvals

ROHS	Conform
------	---------

Downloads

Brochure/Catalogue	CAT 1 TERM 16/17 EN
Engineering Data	EPLAN, WSCAD, Zuken E3.S
Engineering Data	STEP
User Documentation	StorageConditionsTerminalBlocks

Data sheet**Accessories**
TS 35X7.5/LL/6 2M/ST/ZN

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings