

PRODUCT-DETAILS

PKL36-1

COMP PIN TERM 1/0 PIGTAIL .258X6



General Information

Extended Product Type	PKL36-1
Product ID	7TAA267280R0009
EAN	5415022349146
Catalog Description	COMP PIN TERM 1/0 PIGTAIL .258X6
Long Description	Compression Pin Terminal Aluminum, Contax filled for Wire Range 1/0 ASCR, 1/0 Stranded, Pigtail: 0.258 x 6, Mechanical Dies: 840, K840, TX, Hydraulic Dies: 840, B48EA, EEI 11A, K840, U249, 76

Ordering

EAN	5415022349146
-----	---------------

Dimensions

Product Net Weight	.32 lb 145.125 g
--------------------	---------------------

Container Information

Package Level 1 Units	25 piece
Package Level 1 Width	3.4 in 86 mm
Package Level 1 Height	6 in

	152 mm
Package Level 1 Depth / Length	12.2 in 310 mm
Package Level 2 Units	100 piece
Package Level 2 Width	8.3 in 211 mm
Package Level 2 Height	13.5 in 343 mm
Package Level 2 Depth / Length	16.5 in 419 mm

Additional Information

Application	Designed for use in joining Aluminum Secondaries and Services to Copper Transformer Bushings
Brand / Label	Blackburn
Connection Type	Compression
Insulation Material	None
Material	Aluminum Sleeve, Pre-attached Copper Pigtail
Mounting Type	None
Number of Batteries	0
Number of Conductors	2
Pigtail Size	1/4x 6 in
Product Name	ELECTRICAL TERMINAL
Product Type	Pigtail Compression Sleeve
Size	Sleeve Length 3-1/2 inches
Special Functions	Sleeves are Highly Conductive Aluminum. Pigtails are Solid Copper, Tin-Plated. Installed with Standard Tools and Dies. Prefilled with Oxide Inhibitor.
Surface Finishing	Tinplated Pigtail
UPC	783786104130
Voltage Rating	35 kV

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	PKL36-1
Instructions and Manuals	PKL36-1

Classifications

UNSPSC	39121458
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4685 >> Wire or cable compression reducer

Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Distribution Connectors

