



Representative Image

Catalog No. GPS1BSAC

Description: MMS STD BK 0.25 - 0.4 AMPS

UPC No

Home > Starters > IEC > Manual Motor Starter - SURION

- MANUAL MOTOR STARTER T+M PROT. GPS1 0,25-0,4A STAND.BREAKING
- Pack-5

Descriptors

Category	Manual Motor Starter - SURION
GO Schedule	CC

Specifications

Rated Current	0.40 A
Capacity	GPS1BS - Standard breaking capacity
Instantaneous short-circuit release (A)	5.2
Rated power 3 phase motors at 220/230Vac Pn (hp)	0.06 hp
Rated power 3 phase motors at 400Vac Pn (hp)	0.09 hp
Rated power 3 phase motors at 440Vac Pn (hp)	0.09 hp
Rated power 3 phase motors at 500/525Vac Pn (hp)	0.09/0.12 hp
Rated power 3 phase motors at 660/690Vac Pn (hp)	0.12/0.18 hp
Rated service short-circuit breaking cap 220/230V Ics kA	100
Rated service short-circuit breaking cap 400V Ics kA	100
Rated service short-circuit breaking cap 440V Ics kA	100
Rated service short-circuit breaking cap 500/525V Ics kA	100
Rated service short-circuit breaking cap 600V Ics kA	100
Rated service short-circuit breaking cap 690V Ics kA	100
Rated ultimate short-circuit breaking cap 220/230V Icu kA	100
Rated ultimate short-circuit breaking cap 400V Icu kA	100
Rated ultimate short-circuit breaking cap 440V Icu kA	100
Rated ultimate short-circuit breaking cap 500/525V Icu kA	100
Rated ultimate short-circuit breaking cap 600V Icu kA	100
Rated ultimate short-circuit breaking cap 690V Icu kA	100
Series	Surion - GPS1B - Thermal and magnetic protection (Ie max 32A)
Thermal current setting range (A)	0.25 - 0.4 A
Trip class IEC 60947-4-1	Class 10
GSA Compliance	No

Dimensions

Weight	0.62 lb
--------	---------

Dimensions

Width	45.0 mm
-------	---------
