

Eaton M22 modular pushbutton

M22-PV-K12

UPC:786685271767

Dimensions:

- **Height:** 4.69 IN
- **Length:** 1.46 IN
- **Width:** 1.38 IN

Weight:.255 LB

Notes:Positively driven contact blocks.

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Type:** Emergency Stop
- **Action:** Maintained
- **Actuator:** Knob, Push-pull
- **Bezel:** Silver
- **Button Color:** Red
- **Contact Configuration:** 1NO-2NC
- **Environmental Rating:** IP67, IP69K, NEMA 4X, 13
- **Illumination:** Non-illuminated
- **Size:** 22.5 mm
- **Series:** M22

Supporting documents:

- [Eatons Volume 7-Logic Control, Operator Interface and Connectivity Solutions](#)
- [M22-PV_-K_\(3\) 2D PDF](#)
- [M22-PV_-K_\(3\) 3D Model Xchange](#)
- [M22-PV_-K_\(3\) 2D Drawing Xchange](#)
- [M22-PV_-K_\(3\) AutoCAD 2D Footprint](#)
- [M22-PV_-K_\(3\) 3D Inventor](#)



- M22-PV_-K_(3) AutoCAD 2D Footprint (mm)
- M22 Operators and Accessories
- M22 Pilot Devices
- Global Data Sheet - M22-PV-K12
- Eaton Specification Sheet - M22-PV-K12

Certifications:

- CSA Certified
- CCC Marked
- Lloyd's Register Certified

Product compliance:

- Bureau Veritas
- CE Marked
- GoST-R