



PSG120F24RM

UPC:786685683584

Dimensions:

- **Height:** 2.5 IN
- **Length:** 6 IN
- **Width:** 6.5 IN

Weight:1.2 LB

Warranties:

- 3 year

Specifications:

- **Operating Temperature - Max:** 75 C
- **Operating Temperature - Min:** -25 C
- **Enclosure Color:** Aluminum
- **Frequency Rating:** 47-63 Hz
- **Input Voltage:** 400-500Vac
- **Output:** 120W
- **Output Voltage:** 24V
- **Terminals:** Finger-safe
- **Phase:** Three-phase

Supporting documents:

- [Eaton's Volume 7-Logic Control, Operator Interface and Connectivity Solutions](#)
- [PSG120F24RM 3D Model Xchange](#)
- [PSG120F24RM AutoCAD 2D Footprint \(mm\)](#)
- [PSG120F24RM AutoCAD 2D Footprint](#)
- [PSG120F24RM 2D PDF](#)
- [PSG120F24RM 2D Drawing Xchange](#)
- [PSG120F24RM 3D Inventor](#)
- [Installation Instructions for PSG120F Power Supply](#)
- [Eaton's PSG Series Power Supplies](#)
- [Eaton Specification Sheet - PSG120F24RM](#)

Certifications:

- UL 508
- EN Listed
- IEC Rated

- CSA Std. C22.2

Product compliance:

- RoHS Compliant
- CE Marked

© 2016 Eaton. All rights reserved.