STAINLESS & CARBON STEEL VALVES

V400 series valves feature blowout-proof stems and lockable handles. The bodies and balls are investment cast type 316 stainless steel, and the handles and stems are type 304. Seals are teflon, reinforced with glass fibre.

V401... STAINLESS STEEL BALL VALVE

1000 psi water, oil, gas up to 1".
800 psi water, oil, gas 1¼" – 2".
150 psi steam.
Temperature Range -28°C (-20°F) to 232°C (450°F)

Part No.	Pipe Size	IMPA Code	PRICE EACH
V401-025	¼"	75-18-01	$18.20
V401-038	⅜"	75-18-02	19.20
V401-050	½"	75-18-03	21.40
V401-075	¾"	75-18-04	28.70
V401-100	1"	75-18-05	39.10
V401-125	1¼"	75-18-06	60.60
V401-150	1½"	75-18-07	67.30
V401-200	2"	75-18-08	102.80

V402... FULL PORT STAINLESS BALL VALVE

Two piece body with mounting pad.
2000 psi water, oil, gas to 1".
1500 psi 1¼" – 2".
150 psi steam.
Temperature Range -28°C (-20°F) to 232°C (450°F)

V402-025	¼"	39.40
V402-038	⅜"	39.40
V402-050	½"	46.30
V402-075	¾"	60.00
V402-100	1"	84.40
V402-125	1¼"	119.10
V402-150	1½"	167.20
V402-200	2"	233.40

V412... 1000 psi FULL PORT STAINLESS BALL VALVE

Two piece body.
1000 psi water, oil, gas to 2".
150 psi steam.
Temperature Range -28°C (-20°F) to 232°C (450°F)

V412-025	¼"	23.50
V412-038	⅜"	23.50
V412-050	½"	24.90
V412-075	¾"	36.00
V412-100	1"	48.60
V412-125	1¼"	72.80
V412-150	1½"	103.70
V412-200	2"	141.10
V412-300	3"	500.60

V432... THREE-PIECE FULL PORT STAINLESS BALL VALVE

1000 psi water, oil, gas. 150 psi steam.

V432-300	3"	772.70

V601... CARBON STEEL BALL VALVE

2000 psi water, oil, gas. 3000 psi in ⅜" size. 150 psi steam
⅜" size is now plated for extra corrosion resistance. Reduced port, one piece carbon steel body. Type 304 Stainless Steel ball & trim. NACE trim.
Type 316 stainless steel blow-out proof stem. PTFE Teflon® seats & seals.
NPTF female threads.
Temperature Range -28°C (-20°F) to 232°C (450°F)

V601-025	¼"	17.60
V601-038	⅜"	19.80
V601-050	½"	22.60
V601-075	¾"	27.60
V601-100	1"	37.00
V601-125	1¼"	60.70
V601-150	1½"	77.90
V601-200	2"	86.80
V6010RB-050	½" ORB (¾-16)	22.60

Part No.	Pipe Size	Working Pressure	PRICE EACH

V605... HIGH-PRESSURE STEEL BALL VALVE

Plated steel body
POM - poly-oxy-methylene seals (Delrin®)
Temperature range -20°C (-4°F) to 100°C (212°F)
NPTF female threads except where shown

V605 is not designed for use with water.

V605-025	¼"	7250 psi	$23.30
V605-038	⅜"	7250 psi	25.70
V605-050	½"	7250 psi	29.80
V605-075	¾"	5800 psi	49.30
V605-100	1"	5075 psi	65.70
V605-125	1¼"	5075 psi	124.40
V605-150	1½"	5075 psi	180.10
V605-200	2"	5075 psi	245.30
V605SAE-100	1" ORB (1 5/16"-12)	5075 psi	74.50

V605H... REPLACEMENT HANDLES

V605H-025-050	¼" to ½"	6.90
V605H-075-100	¾" & 1"	9.80
V605H-125-200	1¼" to 2"	12.10

STAINLESS BUTTERFLY VALVES

Manufactured from Type 304 Stainless Steel and featuring silicone gaskets, Green Line carries both Three-Position and Multi-Position valves. With a working pressure up to 145 psi, our butterfly valves have a temperature range of -20°C (-4°F) to 135°C (275°F) and come complete with clamp style connections.

Part Number	Fitting Size	PRICE EACH

V53PH... THREE-POSITION PULL HANDLE VALVE

145 psi
Temperature Range -20°C (-4°F) to 135°C (275°F)

V53PH-150	1½"	135.70
V53PH-200	2"	165.90

V53TH... MULTI-POSITION TRIGGER HANDLE VALVE

145 psi
Temperature Range -20°C (-4°F) to 135°C (275°F)

V53TH-150	1½"	135.70
V53TH-200	2"	165.90

12 Valves