
Non-Programmable Thermostats

Mercury Free T822 Econo Thermostats



10 . 20 . 30

Thermostats provide 24 Vac control of heating or cooling systems

· Vented cover for improved temperature sensing

Setting lever and thermometer scale on thermostat face

Mounts directly on the wall or on vertical outlet box

· Integrated thermometer and setting scale

Dimensions, Approximate: 121 mm high x 73 mm wide x 35 mm deep

(4 3/4 in. high x 2 7/8 in. wide x 1 3/8 in. deep)

Mounting: Vertical Sensor Element: Bimetal

Switch Type: Precision Snap Action


Switching Action: SPST Color: Premier White® Accuracy: ± 1 C (± 2 F) Supply Voltage: 20 to 30 Vac

Heating Current: 0.02 A to 1.0 A running

Product Number	Application	Terminal Designations		Setting Temperature Range	Switch Position		
			Stages		System	Fan	Comments
T822K1026/U	Heat Only	R, W	1 Heat	7 C to 32 C	HEAT-OFF	_	with Positive Off
T822K1034/U	Heat Only	R, W	1 Heat	7 C to 32 C	_	_	_
T822K1059/U	Heat Only	R, W, G	1 Heat	7 C to 32 C	_	AUTO-ON	_

20 . 30

Mercury Free T827 Econo Thermostats



Rated for 12 Vdc and millvoltage systems

Coiled bimetal element operates snap-acting switch

Temperature setting lever on bottom of thermostat

Mounting using two screws through base to wall or vertical outlet box

Temperature setting and thermometer scale on cover

Dimensions, Approximate: 121 mm high x 73 mm wide x 35 mm deep (4 3/4 in. high x 2 7/8 in. wide x 1 3/8 in. deep)

Mounting: Vertical

Sensor Element: Bimetal

Switch Type: Precision Snap Action

Switching Action: SPST Color: Premier White® Accuracy: ± 1 C (± 2 F) Supply Voltage: 12 Vdc; 750 mV

Product Number	Application	Terminal Designations	Stages	Setting Temperature Range	Switch Position System	Comments
T827K1017/U	Heat Only	R, W	1 Heat	7 C to 32 C	HEAT-OFF	with Positive Off

70C-6910 Honeywell