

# SMOKE ALARM

## FG250BA

### DUAL IONIZATION

Dual Ionization sensing chamber. Generally more effective at detecting small particles produced by flaming fires. Sources may include paper or kitchen grease.

### SILENCE FEATURE

Silences nuisance alarms.

### HINGED COVER DESIGN

Fast and easy installation and battery replacement

### TAMPER RESISTANT LOCKING PIN

Locks alarm cover to prevent removal of battery. Perfect for apartment, dormitory or hotel applications.

### 9V BATTERY INCLUDED

### APPROVED FOR RV USE



**IONIZATION ALARM**

### DESCRIPTION:

The FG250 is a single station smoke alarm specifically designed for residential and institutional applications including sleeping rooms of hospitals, hotels, motels, dormitories, and other multifamily dwellings as defined in standard NFPA 101. The compact, low profile design complements any décor. Battery installation and removal can occur while the unit is mounted to the ceiling or wall via the hinged cover. When voltage drops to a pre-set warning level, the horn will “chirp” approximately once per minute to indicate a fresh battery is needed. To ensure the battery is always replaced properly, the cover is designed to resist closing when the battery is missing. Designed for wall or ceiling mounting. Includes mounting anchors and screws.



### TECHNICAL SPECS

|                              |                                                                     |
|------------------------------|---------------------------------------------------------------------|
| Alarm Dimensions:            | 4.25" dia x 1.6"H                                                   |
| Weight:                      | 4.8 oz.                                                             |
| Operating Voltage:           | 9V Battery Powered                                                  |
| Temperature Range:           | 40°F (4°C) to 100°F (38°C)                                          |
| Humidity Range:              | 10% to 95% relative humidity (RH)                                   |
| Audio Alarm:                 | 85dB at 10 feet                                                     |
| Test/Silence:                | Electronically simulates smoke condition, causing the unit to alarm |
| Alarm Reset:                 | Automatic when smoke clears                                         |
| Smoke Sensor:                | Dual Ionization                                                     |
| Indicator Lights (DC Power): | Intermittent Red Light                                              |
| Listing:                     | cETL to ULC-S531                                                    |

### SHIPPING SPECS

|                                     |                                   |
|-------------------------------------|-----------------------------------|
| Individual:                         | Materpack: 6                      |
| Dimensions: 1.75W x 4.375L x 4.375H | Dimensions: 9.6"L x 4.8"H x 5.7"W |
| UPC: 029054012982                   | UPC: 20029054012986               |

# 10 YEAR WARRANTY