



## A19 REPLACEMENT : E26 & GU24 BASE

### DESCRIPTION

LED A-Line Replacement Lamps directly replace incandescent A lamps at a fraction of the energy cost.

### FEATURES

- Direct replacement for 40W, 60W, 75W, or 100W incandescent A-lamps
- 240° beam angle is ideal for table lamps, wall sconces, and luminous globe fixtures
- 80% more efficient and 30x longer life than standard incandescent
- Shatter-resistant plastic housing for reduced risk of injury and breakage
- Dimmable models compatible with a wide array of dimmers
- ANSI construction compliant
- Not for use with electronic timers, photocells, or motion/occupancy sensors

### WARRANTY

- 5 year limited warranty; see eiko.com for warranty details

### APPLICATIONS

- Restaurants & Hospitality
- Retail
- Residential
- Accent/Display Lighting
- Healthcare



A19 E26



A19 GU24



<b>PERFORMANCE</b>	Power Consumption	5.5W	8W	11W	13W
	Lumens	450	800	1,100	1,600
	Efficacy (LPW)	82	100	100	123
	CRI	80+			
	Beam	240°			
	CCT	2700K/3000K/4000K/5000K			
	Life (L70)				
<b>ELECTRICAL</b>	Power Factor	>0.7			
	Input Voltage	120V			
<b>CONSTRUCTION</b>	Operating Temperature	-4°F to 104°F (-20°C to 40°C)			
	Base	E26/GU24			
<b>LISTINGS</b>	Certification(s)	ENERGY STAR® Rated; cULus Classified			
	Material Usage	RoHS Compliant; no mercury or lead			
	Environment	Suitable for damp locations; Enclosed fixture rated			

## PERFORMANCE SUMMARY

### A19 MEDIUM BASE (E26):

Order Code	Item #	Lumens	Watts	LPW	CCT	CRI	Beam	MOL	MOD	Life/Hours	Replaces Incan.	ES
11067	LED5.5WA19/OMN/827-DIM-B	450	5.5W	82	2700K	80+	240°	4.25"	2.36"	25,000	40W A19	★
11068	LED5.5WA19/OMN/830-DIM-B	450	5.5W	82	3000K	80+	240°	4.25"	2.36"	25,000	40W A19	★
11069	LED5.5WA19/OMN/840-DIM-B	450	5.5W	82	4000K	80+	240°	4.25"	2.36"	25,000	40W A19	★
11070	LED8WA19/OMN/827-B	800	8W	100	2700K	80+	240°	4.25"	2.36"	25,000	60W A19	★
11071	LED8WA19/OMN/830-B	800	8W	100	3000K	80+	240°	4.25"	2.36"	25,000	60W A19	★
11072	LED8WA19/OMN/840-B	800	8W	100	4000K	80+	240°	4.25"	2.36"	25,000	60W A19	★
11073	LED8WA19/OMN/850-B	800	8W	100	5000K	80+	240°	4.25"	2.36"	25,000	60W A19	★
11074	LED8WA19/OMN/827-DIM-B	800	8W	100	2700K	80+	240°	4.25"	2.36"	25,000	60W A19	★
11075	LED8WA19/OMN/830-DIM-B	800	8W	100	3000K	80+	240°	4.25"	2.36"	25,000	60W A19	★
11076	LED8WA19/OMN/840-DIM-B	800	8W	100	4000K	80+	240°	4.25"	2.36"	25,000	60W A19	★
11077	LED8WA19/OMN/850-DIM-B	800	8W	100	5000K	80+	240°	4.25"	2.36"	25,000	60W A19	★
11081	LED11WA19/OMN/827-DIM-B	1,100	11W	100	2700K	80+	240°	4.25"	2.36"	25,000	75W A19	★
11082	LED11WA19/OMN/830-DIM-B	1,100	11W	100	3000K	80+	240°	4.25"	2.36"	25,000	75W A19	★
11083	LED11WA19/OMN/840-DIM-B	1,100	11W	100	4000K	80+	240°	4.25"	2.36"	25,000	75W A19	★
11084	LED11WA19/OMN/850-DIM-B	1,100	11W	100	5000K	80+	240°	4.25"	2.36"	25,000	75W A19	★
11088	LED13WA19/OMN/827-DIM-B	1,600	13W	123	2700K	80+	240°	4.6"	2.36"	25,000	100W A19	★
11089	LED13WA19/OMN/830-DIM-B	1,600	13W	123	3000K	80+	240°	4.6"	2.36"	25,000	100W A19	★
11090	LED13WA19/OMN/840-DIM-B	1,600	13W	123	4000K	80+	240°	4.6"	2.36"	25,000	100W A19	★
11091	LED13WA19/OMN/850-DIM-B	1,600	13W	123	5000K	80+	240°	4.6"	2.36"	25,000	100W A19	★

### A19 GU24 BASE:

Order Code	Item #	Lumens	Watts	LPW	CCT	CRI	Beam	MOL	MOD	Life/Hours	Replaces Incan.	ES
11078	LED8WA19/OMN/827-GU24-DIM-B	800	8W	100	2700K	80+	240°	4.25"	2.36"	25,000	60W A19	★
11079	LED8WA19/OMN/830-GU24-DIM-B	800	8W	100	3000K	80+	240°	4.25"	2.36"	25,000	60W A19	★
11080	LED8WA19/OMN/840-GU24-DIM-B	800	8W	100	4000K	80+	240°	4.25"	2.36"	25,000	60W A19	★
11085	LED11WA19/OMN/827-GU24-DIM-B	1,100	11W	100	2700K	80+	240°	4.25"	2.36"	25,000	75W A19	★
11086	LED11WA19/OMN/830-GU24-DIM-B	1,100	11W	100	3000K	80+	240°	4.25"	2.36"	25,000	75W A19	★
11087	LED11WA19/OMN/840-GU24-DIM-B	1,100	11W	100	4000K	80+	240°	4.25"	2.36"	25,000	75W A19	★

NOTE: Use order code when ordering. ★ENERGY STAR® Rated

## DIMENSIONS



# DIMMER COMPATIBILITY

Manufacturer	Part Number	5.5W 450 lm	8W 800 lm	11W 1,100 lm	13W 1,600 lm
ADORNE	ADPD453LW2	✓	✓	✓	✗
ADORNE	ADWR703HW4	✓	✓	✓	✗
AH	SDM/600/WHTTE 600W	✓	✓	✓	✗
ALMOND	LUXDM600-12 600W	✓	✓	✓	✗
COOPER	DAL06P-C2-K	✗	✗	✗	✗
COOPER	TAL06P-C2-K	✗	✗	✗	✗
COOPER	SAL06P-W-K	✗	✗	✗	✗
CTL	DM600-12-3 600W	✓	✓	✓	✓
EATON	TAL06P1-C5	✗	✗	✗	✗
EATON	AAL06-C1	✗	✗	✗	✗
EATON	SAL06P-LA-K	✗	✗	✗	✗
GE	18024 600W	✗	✗	✗	✗
HALO	SAL06P-W-HALOGF2	✗	✗	✗	✗
LEGRAND	HCL453PTC	✓	✓	✓	✓
LEGRAND	RHCL453PW	✓	✓	✓	✓
LEVITON	6684 600W	✓	✓	✓	✗
LEVITON	6631-LA 600W	✓	✓	✓	✓
LEVITON	IPI06 600W	✗	✗	✗	✓
LEVITON	S-600P-WH	✗	✗	✗	✗
LEVITON	LIGHT ALMOND NO.6672 600W	✓	✓	✓	✓
LEVITON	603-6631-A 600W	✓	✓	✓	✗
LEVITON	6631-A 600W	✓	✓	✓	✗
LEVITON	White/Lvory/Light Almond IPI10-1LZ 600W	✗	✗	✗	✗
LEVITON	WHITE NO.6674 600W	✗	✗	✗	✓
LEVITON	LIGHT ALMOND NO.6681 600W	✗	✗	✗	✓
LEVITON	6683-10Z 600W	✓	✓	✓	✗
LEVITON	IPI06-1LZ 600W	✓	✓	✓	✓
LEVITON	WHITE NO.6631 600W	✓	✓	✓	✓
LEVITON	6681	✓	✓	✓	✗
LUTRON	DV-603P600W	✗	✗	✗	✓
LUTRON	S-600 600W	✓	✓	✓	✓
LUTRON	LGCL-153CL 600W	✗	✗	✗	✗
LUTRON	CT-103P-WH 1000W	✓	✓	✓	✓
LUTRON	CTCL-153P-WH 600W	✗	✗	✗	✗
LUTRON	TGCL-153PH-WH 600W	✗	✗	✗	✓
LUTRON	D-600PH-DK 600W	✓	✓	✓	✓
LUTRON	DV-603PR 600W	✗	✗	✗	✗
LUTRON	S-600PR-WH 600W	✗	✗	✗	✗
LUTRON	DVWCL-153PH-WH 600W	✗	✗	✗	✓
LUTRON	DVW-600PH-WH 600W	✗	✗	✗	✗
LUTRON	DV-603PH-WH 600W	✓	✓	✓	✓
LUTRON	DV-600PH-WH 600W	✓	✓	✓	✓
LUTRON	S-603PGH-WH 600W	✗	✗	✗	✗
LUTRON	WHITE NO.IPL06 600W	✓	✓	✓	✓
LUTRON	S-600H-WH 600W	✓	✓	✓	✓
LUTRON	S-10PH 1000W	✓	✓	✓	✓
LUTRON	D-600RH-DK 600W	✓	✓	✓	✓
LUTRON	TG-600PH-WH 600W	✗	✗	✗	✓
LUTRON	TG-600PH-IV 600W	✓	✓	✓	✗
LUTRON	CT-600PR-WH 600W GC	✗	✗	✗	✓