

T8

35T8/96-4000 IF FA8 10/1

Our TLEDs are available in InstantFit (Type A / Type C) or MainsFit (Ballast bypass / Type B) versions. The InstantFit lamps work on a broad variety of ballasts and LED drivers. Only InstantFit has over 15,000 lamp & ballast combinations delivering even light output, energy savings and a long lifetime. Our MainsFit products feature a double-ended design, simplifying installation while a proprietary safety circuit minimizes a shock risk. Lamp sizes range from 2-foot to 8-foot and U-bend with a variety of lumen outputs.

Product data

| General Information | | Lamp Current (Max) | |
|---------------------------------------|---------------------------|---------------------------------|---------------------------|
| Base | FA8 [FA8] | | 260 mA |
| EU RoHS compliant | Yes | Lamp Current (Min) | 160 mA |
| Nominal Lifetime (Nom) | 50000 h | Warm Up Time to 60% Light (Nom) | 0.5 s |
| Switching Cycle | 50000X | UL Type | Type A - works on ballast |
| | | Power Factor (Nom) | 0.9 |
| | | Voltage (Nom) | 280-410 V |
| Light Technical | | Temperature | |
| Color Code | 841 [CCT of 4100K (841)] | T-Ambient (Max) | 45 °C |
| Beam Angle (Nom) | 180 ° | T-Ambient (Min) | -20 °C |
| Initial lumen (Nom) | 4200 lm | T-Storage (Max) | 65 °C |
| Color Designation | Cool White (CW) | T-Storage (Min) | -40 °C |
| Correlated Color Temperature (Nom) | 4000 K | T-Case Maximum (Nom) | 45 °C |
| Luminous Efficacy (rated) (Nom) | 120.00 lm/W | | |
| Color Consistency | <6 | Controls and Dimming | |
| Color Rendering Index (Nom) | 82 | Dimmable | No |
| LLMF At End Of Nominal Lifetime (Nom) | 70 % | | |
| Operating and Electrical | | Mechanical and Housing | |
| Input Frequency | 50000-64000 Hz | Bulb Material | Plastic |
| Power (Rated) (Nom) | 35 W | Product Length | 96 in |


T8

| | |
|---------------------------------|--------------------|
| Bulb Shape | Tube, double-ended |
| Approval and Application | |
| Energy Efficiency Label (EEL) | Not applicable |
| Energy Saving Product | Yes |
| Approbation Marks | UL certificate |
| Energy Consumption kWh/1000 h | - kWh |

| | |
|---------------------|--------------------------|
| Product Data | |
| Order product name | 35T8/96-4000 IF FA8 10/1 |

| | |
|---------------------------------|--------------|
| EAN/UPC - Product | 046677472580 |
| Order code | 469254 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 10 |
| Material Nr. (12NC) | 929001314604 |
| Net Weight (Piece) | 0.540 kg |
| Model Number | 9290013146 |


Dimensional drawing




TLED Ess IF 3200lm 4000K 8ft single pin

| Product | D | A1 | A2 | A3 |
|--------------------------|---------|-----------|-----------|-----------|
| 35T8/96-4000 IF FA8 10/1 | 27.9 mm | 2366.9 mm | 2375.2 mm | 2383.5 mm |

Photometric data




TLED Ess 35W FA8 840 4200lm T8



TLED Ess 35W FA8 840 4200lm T8


T8

Photometric data



TLED Ess 35W FA8 840 4200lm T8

Lifetime



TLED Ess 35W FA8 T8 IF

TLED Ess 35W FA8 T8 IF

