Universal Guards





On/Off Relays

| Product # Price Volts 60 Hz Resistive Charge (A) Without transformer RC840 40.00 120/208/240 347 18 R841D1036 77.00 600 10 With transformer RC840T-120 76.00 120 22 RC840T-240 54.00 208/240 22 RC840T-347 55.00 347 18 R841C1151 89.00 600 10 | | | | |
|--|--------------------|-------|-------------|----------------------|
| RC840 40.00 120/208/240 347 18 R841D1036 77.00 600 10 With transformer RC840T-120 76.00 120 22 RC840T-240 54.00 208/240 22 RC840T-347 55.00 347 18 | Product # | Price | | Resistive Charge (A) |
| RC840 40.00 347 18 R841D1036 77.00 600 10 With transformer RC840T-120 76.00 120 22 RC840T-240 54.00 208/240 22 RC840T-347 55.00 347 18 | Without transforme | er | | |
| 347 18 18 18 19 19 19 1 | DC940 | 40.00 | 120/208/240 | 22 |
| With transformer RC840T-120 76.00 120 22 RC840T-240 54.00 208/240 22 RC840T-347 55.00 347 18 | NC040 | | 347 | 18 |
| RC840T-120 76.00 120 22 RC840T-240 54.00 208/240 22 RC840T-347 55.00 347 18 | R841D1036 | 77.00 | 600 | 10 |
| RC840T-240 54.00 208/240 22 RC840T-347 55.00 347 18 | With transformer | | | |
| RC840T-347 55.00 347 18 | RC840T-120 | 76.00 | 120 | 22 |
| 3.00 | RC840T-240 | 54.00 | 208/240 | 22 |
| R841C1151 89.00 600 10 | RC840T-347 | 55.00 | 347 | 18 |
| | R841C1151 | 89.00 | 600 | 10 |

Note: Not recommended for fast-cycling modulated regulation (more than 6 cycles/hr). For fast-cycling heating equipment Solid State Relay.

Meant for external installation only. For installation inside heaters, refer to the options table

of the concerned product series.

Triac Relays

| Product # | Price | Volts 60 Hz | Resistive Charge (A) | Input Signal | | |
|---------------------|--------|-----------------|-------------------------|----------------------|--|--|
| Without transformer | | | | | | |
| RT850 | 58.00 | 100 to 347 | 23 | 4-32VDC, 24VAC | | |
| CCT-25-1-C1 | 100.00 | 208/240/347 | 25 | 3-32VDC, 24VAC | | |
| CCT-30-1-C2 | 129.00 | 48-600 | 30 | 3-32VDC, 24VAC | | |
| With transformer | | | | | | |
| RT850T-240 | 69.00 | 208/240 | 23 | 19.2/24VAC | | |
| RT850T-347 | 65.00 | 347 | 23 | 24VAC | | |
| CCT-25-1-C2-T | 100.00 | 208/240/277/347 | 25 | 14.4/16.6/19.2/24VAC | | |

Note: Meant for external installation only. For installation inside heaters, refer to the options table of the concerned product series.

Universal Guards

| Pro | oduct# | Price | Description | Inside Dimension (Length X Height X Depth) |
|-----|--------|-------|------------------------|---|
| F29 | 9-0143 | 39.00 | Clear plastic | 6 3/8 in. X 3 1/2 in. X 3 in. |
| F29 | 9-0198 | 39.00 | thermostat guard | 8 1/4 in. X 5 3/8 in. X 3 1/2 in. |
| F29 | 9-0193 | 63.00 | Metal thermostat guard | 6 in. X 3 13/16 in. X 3 1/8 in. |