

Eaton M22 modular pushbutton

M22-PVL-K01-230R

UPC:786685271774

Dimensions:

- **Height:** 3.66 IN
- **Length:** 1.46 IN
- **Width:** 1.38 IN

Weight:.128 LB

Notes:Positively driven contact blocks.

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Type:** Emergency Stop
- **Action:** Maintained
- **Actuator:** Knob, Push-pull
- **Bezel:** Silver
- **Button Color:** Red
- **Contact Configuration:** 1NC
- **Environmental Rating:** IP67, IP69K, NEMA 4X, 13
- **Illumination:** Illuminated
- **Size:** 22.5 mm
- **Series:** M22
- **Voltage Rating:** 85-264V

Supporting documents:

- [Eatons Volume 7-Logic Control, Operator Interface and Connectivity Solutions](#)
- [M22-PV_-K_\(1\) 3D Model Xchange](#)
- [M22-PV_-K_\(1\) AutoCAD 2D Footprint \(mm\)](#)
- [M22-PV_-K_\(1\) 2D PDF](#)
- [M22-PV_-K_\(1\) 2D Drawing Xchange](#)



- M22-PV_-K_(1) AutoCAD 2D Footprint
- M22-PV_-K_(1) 3D Inventor
- M22 Operators and Accessories
- M22 Pilot Devices
- Eaton Specification Sheet - M22-PVL-K01-230R

Certifications:

- CSA Certified
- CCC Marked
- Lloyd's Register Certified

Product compliance:

- GoST-R
- CE Marked
- Bureau Veritas