

PSG960F24RM

UPC:786685683614

Dimensions:

- **Height:** 8 IN
- **Length:** 6.5 IN
- **Width:** 6.25 IN

Weight:4.81 LB

Warranties: No Data

Specifications:

- **Wattage:** 960W
- **Operating Temperature - Max:** 75 C
- **Operating Temperature - Min:** -20 C
- **Enclosure Material:** Aluminum
- **Frequency Rating:** 47-63 Hz
- **Input Voltage:** 400-500 Vac
- **Nominal Voltage:** 24 Vdc (± 4.8 Vdc)
- **Output:** 24 Vdc/2.5A
- **Output Voltage:** 24V
- **Phase:** Three-phase

Supporting documents:

- [PSG960F24RM 2D Drawing Xchange](#)
- [PSG960F24RM 2D PDF](#)
- [PSG960F24RM 3D Model Xchange](#)
- [PSG960F24RM AutoCAD 2D Footprint](#)
- [PSG960F24RM AutoCAD 2D Footprint \(mm\)](#)
- [PSG960F24RM 3D Inventor](#)

Certifications:

- UL 508
- SELV (EN 60950)
- EN 61000-4-11
- cULus/UL 60950-1
- EN 50178
- PELV (EN 60204)
- EN 60204
- EN 61000-4-2
- EN 61000-406



- CSA Certified
- EN 61000-6-2
- IEC Rated
- EN 61000-6-4
- EN 610003-2

Product compliance:

- German Safety
- CE Marked
- RoHS Compliant
- DIN 57100-410

© 2016 Eaton. All rights reserved.