

CWP03 60W Wall Pack, HV

CWP03 Wall Packs Ideal for security, warehouse, and entryway lighting



High impact polycarbonate optics for precision beam control and vandal resistance

Purpose-built LED driver inside





TECHNICAL DATA



LIGHT SPECIFICATIONS

Lumens	8,195 lm
Efficacy	136.92 lm/W
CCT	5000K
CRI	80
Dimmable	0-10V
Warranty	10-year


APPROVALS AND LISTINGS

cUL	E482965
DLC	P99WBP0U

ILLUMINANCE AT A DISTANCE

Illuminance at a Distance				
Center Beam fc	Beam Width			
183.8 fc 🥒	9.3 ft	7.9 ft		
46.0 fc	18.5 ft	15.8 ft		
20.4 fc	27.8 ft	23.7 ft		
11.5 fc	37.1 ft	31.6 ft		
7.4 fc	46.3 ft	39.5 ft		
5.1 fc	55.6 ft	47.5 ft		
19.8R Vert. Spread: 109.1°				
	Center Beam fc 183.8 fc 46.0 fc 20.4 fc 11.5 fc 7.4 fc 5.1 fc	Center Beam fc Beam With 183.8 fc 9.3 ft 46.0 fc 18.5 ft 20.4 fc 27.8 ft 11.5 fc 37.1 ft 7.4 fc 46.3 ft 5.1 fc 55.6 ft		

ISOCANDELA PLOT




ELECTRICAL

Wattage	60W
Voltage	277-480V
Power factor	0.9
THD	15.02%
Operating temp	-40° to 40°C

CONSTRUCTION

Housing	Aluminum / Polycarbonate
Colour	Bronze
IP rating	IP65
Weight	6.45 lbs
Carton qty	1

DIMENSIONS





Western Canada Warehouse: 121-1647 Broadway Street, Port Coguitlam, BC V3C 6P8 | ordersbc@csc-led.com



8-540 Jamieson Parkway, Cambridge, ON Canada N3C 0G5 P: 519.880.9833 888.900.9885 E: info@csc-led.com orders@csc-led.com