

Product Selection

CDD321FDKW



240 Vac Heavy Duty Double Door, Fusible—NEMA 12/3R, 4X

| System | Ampere Rating | Fuse Type Provision | Maximum hp Ratings with Time Delay Fuses | | | | | | NEMA 12/3R Enclosure Dust-tight Catalogue Number | NEMA 4X Enclosure Watertight Catalogue Number |
|--|---------------|---------------------|--|------|----------------|------|------|------|--|---|
| | | | Single-Phase AC | | Three-Phase AC | | DC | | | |
| | | | 480V | 600V | 480V | 600V | 250V | 600V | | |
| Three-Pole, 240 Vac, 250 Vdc (Suitable for Service Entrance Use with a Neutral Kit Factory Installed) | | | | | | | | | | |
| | 30 | H | 7.5 | 10 | 15 | 20 | — | — | CDD321FDKW | CDD321FWKW |
| | 60 | H | 20 | 25 | 30 | 50 | — | — | CDD322FDKW | CDD322FWKW |
| | 100 | H | 30 | 40 | 60 | 75 | — | — | CDD323FDKW | CDD323FWKW |
| | 200 | H | 50 | 50 | 125 | 150 | — | — | CDD324FDKW | CDD324FWKW |
| | 400 | H | — | — | 250 | 350 | — | — | CDD325FDKW | CDD325FWKW |
| | 600 | H | — | — | 400 | 500 | — | — | CDD326FDKW | CDD326FWKW |
| | 800 | L | — | — | 500 | 500 | — | — | CDD327FDKW | CDD327FWKW |
| | 1200 | L | — | — | 500 | 500 | — | — | CDD328FDKW | CDD328FWKW |
| Four-Wire (Three Blades, Three Fuses, S/N) 240 Vac, 250 Vdc | | | | | | | | | | |
| | 30 | H | 7.5 | 10 | 15 | 20 | — | — | CDD321NDKW | CDD321NWKW |
| | 60 | H | 20 | 25 | 30 | 50 | — | — | CDD322NDKW | CDD322NWKW |
| | 100 | H | 30 | 40 | 60 | 75 | — | — | CDD323NDKW | CDD323NWKW |
| | 200 | H | 50 | 50 | 125 | 150 | — | — | CDD324NDKW | CDD324NWKW |
| | 400 | H | — | — | 250 | 350 | — | — | CDD325NDKW | CDD325NWKW |
| | 600 | H | — | — | 400 | 500 | — | — | CDD326NDKW | CDD326NWKW |
| | 800 | L | — | — | 500 | 500 | — | — | CDD327NDKW | CDD327NWKW |
| | 1200 | L | — | — | 500 | 500 | — | — | CDD328NDKW | CDD328NWKW |

CDD361FDKW



600 Vac Heavy Duty Double Door, Fusible—NEMA 12/3R, 4X

| System | Ampere Rating | Fuse Type Provision | Maximum hp Ratings with Time Delay Fuses | | | | | | NEMA 12/3R Enclosure Dust-tight Catalogue Number | NEMA 4X Enclosure Watertight Catalogue Number |
|--|---------------|---------------------|--|------|----------------|------|------|------|--|---|
| | | | Single-Phase AC | | Three-Phase AC | | DC | | | |
| | | | 480V | 600V | 480V | 600V | 250V | 600V | | |
| Three-Pole, 480 Vac–600 Vac or Vdc (Suitable for Service Entrance Use with a Neutral Kit Factory Installed) | | | | | | | | | | |
| | 30 | H | 7.5 | 10 | 15 | 20 | — | — | CDD361FDKW | CDD361FWKW |
| | 60 | H | 20 | 25 | 30 | 50 | — | — | CDD362FDKW | CDD362FWKW |
| | 100 | H | 30 | 40 | 60 | 75 | — | — | CDD363FDKW | CDD363FWKW |
| | 200 | H | 50 | 50 | 125 | 150 | — | — | CDD364FDKW | CDD364FWKW |
| | 400 | H | — | — | 250 | 350 | — | — | CDD365FDKW | CDD365FWKW |
| | 600 | H | — | — | 400 | 500 | — | — | CDD366FDKW | CDD366FWKW |
| | 800 | L | — | — | 500 | 500 | — | — | CDD367FDKW | CDD367FWKW |
| | 1200 | L | — | — | 500 | 500 | — | — | CDD368FDKW ① | CDD368FWKW ① |
| Four-Wire (Three Blades, Three Fuses, S/N) 480 Vac–600 Vac, 250 Vdc | | | | | | | | | | |
| | 30 | H | 7.5 | 10 | 15 | 20 | — | — | CDD361NDKW | CDD361NWKW |
| | 60 | H | 20 | 25 | 30 | 50 | — | — | CDD362NDKW | CDD362NWKW |
| | 100 | H | 30 | 40 | 60 | 75 | — | — | CDD363NDKW | CDD363NWKW |
| | 200 | H | 50 | 50 | 125 | 150 | — | — | CDD364NDKW | CDD364NWKW |
| | 400 | H | — | — | 250 | 350 | — | — | CDD365NDKW | CDD365NWKW |
| | 600 | H | — | — | 400 | 500 | — | — | CDD366NDKW | CDD366NWKW |
| | 800 | L | — | — | 500 | 500 | — | — | CDD367NDKW | CDD367NWKW |
| | 1200 | L | — | — | 500 | 500 | — | — | CDD368NDKW ① | CDD368NWKW ① |

① 1200A is not service entrance rated at 600V.