

Non-combination (main lug only) single-phase Type 3R

Three-Wire 120/240 Vac non-combination Type 3R (outdoor/raintight) ^a



RCBRPL112

Table 6a. Main lug only outdoor/ raintight Type 3R BR plug-on neutral loadcentres ^a

Maximum ampere rating	Catalogue number	Max. no. 1-inch spaces	Max. no. 1/2-inch spaces	Cover Style	Dimensions (inches)			Wire size range for main Cu/Al
					H	W	D	
125	RCBRPL112 ^b	12	24	Outdoor	16-1/2	14-3/8	5	#14-2/0
125	RCBRPL130 ^b	30	60	Outdoor	28-7/8	14-3/8	5	#14-2/0
200	RCBRPL240 ^b	40	80	Outdoor	33-7/8	14-3/8	5	#1-250 MCM

Table 6b. Main lug only outdoor/ raintight Type 3R BR non plug-on neutral loadcentres ^a

Maximum ampere rating	Catalogue number	Max. no. 1-inch spaces	Max. no. 1/2-inch spaces	Cover Style	Dimensions (inches)			Wire size range for main Cu/Al
					H	W	D	
125	RCCPL102 ^b	2	4	Outdoor	11-1/2	6-1/2	4	#14-2/0
125	RCCPL104A ^b	4	8	Outdoor	11-1/2	6-1/2	4	#14-2/0
125	RCCPL108 ^b	8	16	Outdoor	13	11	3-1/2	#14-2/0

^a Outdoor loadcentres accommodate Type DS conduit hubs. Hubs not included. See **page 15** for selection.

^b All enclosures include a locking hasp as an integral part of the door latching mechanism.