

Technical Specification Sheet

3M™ Aura™ Particulate Respirator, 9205+, N95

Key Features

- NIOSH-approved N95 rating
- Adjustable nose clip
- Nose foam
- 3-Panel, flat-fold style
- Stapled headbands
- Individually packed

Material Composition

- Straps – Polyisoprene
- Staples – Steel
- Nose clip – Aluminum
- Nose foam – Polyurethane
- Filter – Polypropylene
- Coverweb – Polypropylene
- This respirator contains no components made from natural rubber latex
- Approximate weight of product: 9.92 g (0.35 oz)
- See the 3M Technical Bulletin – [Cellulose Certification – Filtering Facepiece Respirators](#) for information about which 3M respirators contain cellulose

Country of Origin

Made in Canada

Use For

- Use for solid particulates and liquid mists in concentrations not exceeding 10X PEL/OEL
- Always follow *User Instructions* and use in manners as indicated



Do not use for

- **Do not** use for gases and vapours, oil aerosols, asbestos, arsenic, cadmium, lead, 4,4-methylene dianiline (MDA), or abrasive blasting (unless physically separated from the blasting)
- **Do not** use for particulate concentrations exceeding 10X PEL/OEL
- **Do not** use in any manner not indicated in the *User Instructions*

Approvals and Standards

- NIOSH-approved N95 particulate respirator
- Meets NIOSH 42 CFR 84 N95 requirements for a minimum 95% filtration efficiency against solid and liquid aerosols that do not contain oil
- NIOSH approval number: TC-84A-8590
- Assigned Protection Factor (APF 10) per US OSHA and Canada CSA Z94.4

Time Use Limitation

Replace the respirator when it becomes dirty, damaged, or difficult to breathe through.

Shelf Life and Storage

- 5 years from the date of manufacture
- Use By date on box in MM/YYYY format
- Store respirators in the original packaging, away from contaminated areas, dust, sunlight, extreme temperatures, excessive moisture, and damaging chemicals
- Store in temperatures between -20°C (-4°F) and +30°C (+86°F) and not exceeding 80% RH

WARNING!

These respirators help reduce exposures to certain airborne contaminants. Before use, the wearer must read and understand the User Instructions provided as a part of the product packaging. A written respiratory protection program must be implemented meeting all the requirements of the authority having jurisdiction in your region and/or CSA Standard Z94.4 including training, user screening/medical assessment, and fit testing. **Misuse may result in sickness or death.** For proper use, see package instructions, supervisor, or call 3M Personal Safety Division Technical Service in Canada at 1-800-267-4414.



Available for sale in Canada from:



3M Personal Safety Division
3M Canada
P.O. Box 5757
London, ON N6A 4T1
Canada
1-800-267-4414
3M.ca/Safety

For More Information
Technical Service: 1-800-267-4414
Customer Service: 1-800-364-3577
3M.ca/Safety

Acceptable Fit Test Protocols

Fit Test Protocol*		Acceptable with this product?
Qualitative Protocols	Saccharin	X
	Bitrex™	X
	Irritant Smoke	
	Isoamyl Acetate	
Quantitative Protocols	TSI Portacount	X
	OHD Quantifit	

*Refer to CSA Z94.4

3M PSD products are occupational use only.

3M, 3M Science, Applied to Life, and Aura are trademarks of 3M. Used under license in Canada. © 2020, 3M. All rights reserved. Bitrex is a trademark of the Johnson Matthey Group of Companies. PortaCount is a registered trademark of TSI Incorporated. Quantifit is a copyright of ODH. 2012-19108 E