

# CWP04 Wall Pack

## 60W | Colour Tunable | 120-347V



Ideal for entryway and exterior security lighting

Easy installation and maintenance with colour temperature and voltage options



•CSCLED

www.csc-led.com

### **TECHNICAL DATA**



#### LIGHT SPECIFICATIONS

Lumens	8,208 lm
Efficacy	139.5 lm/W
CCT	3000K / 4000K / 5000K
CRI	82
Dimmable	0-10V
L70 Life	50,000 hrs
Warranty	10-year


#### APPROVALS AND LISTINGS

cUL	E482965
DLC	PLLOJVTP6PYH

#### **ILLUMINANCE AT A DISTANCE**

Illuminance at a Distance				
	Center Beam fc	Beam Wi	dth	
17.0ft	5.33 fc 🖊	36.5 ft	39.0 ft	
34.0R	1.33 fc	73.1 ft	77.9 ft	
51.0R	0.59 fc	109.6 ft	116.9 ft	
68.0R	0.33 fc	146.2 ft	155.8 ft	
85.0R	0.21 fc	182.7 ft	194.8 ft	
102.0R	0.15 fc	219.3 ft	233.7 ft	
	Vert. Spread: 94.1° Horiz. Spread: 97.8°			

#### **ISOCANDELA PLOT**



#### ELECTRICAL

Wattage	60W
Voltage	120-347V
Power Factor	0.9
THD	15%
Operating Temp	-40 to 50°C

#### CONSTRUCTION


Housing	Die-Cast Aluminum
Cover	Borosilicate Glass
Finish	Bronze
IP Rating	IP65
Net Weight	3.5 kg
Gross Weight	4.5 kg
Carton Qty	1
Carton Dimensions	397 x 297 x 250 mm

#### ACCESSORIES (Ordered Separately)

Visor	CWP04-VISOR
Motion Sensor	HB01DMS-C
Remote	HB01R
Wireguard	CWP04-WG

**Note:** HB01R (remote) is **required** for HB01DMS-C (motion sensor)

#### DIMENSIONS



Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | ordersbc@csc-led.com



8-540 Jamieson Parkway, Cambridge, ON Canada N3C 0G5 P: 519.880.9833 888.900.9885 E: info@csc-led.com orders@csc-led.com