

## Non-combination (main lug only) single-phase Type 3R

Three-Wire 120/240 Vac non-combination Type 3R (outdoor/raintight) <sup>a</sup>



RCBRPL112

**Table 6a. Main lug only outdoor/ raintight Type 3R BR plug-on neutral loadcentres <sup>a</sup>**

Maximum ampere rating	Catalogue number	Max. no. 1-inch spaces	Max. no. 1/2-inch spaces	Cover Style	Dimensions (inches)			Wire size range for main Cu/Al
					H	W	D	
125	RCBRPL112 <sup>b</sup>	12	24	Outdoor	16-1/2	14-3/8	5	#14–2/0
125	RCBRPL130 <sup>b</sup>	30	60	Outdoor	28-7/8	14-3/8	5	#14–2/0
200	RCBRPL240 <sup>b</sup>	40	80	Outdoor	33-7/8	14-3/8	5	#1–250 MCM

**Table 6b. Main lug only outdoor/ raintight Type 3R BR non plug-on neutral loadcentres <sup>a</sup>**

Maximum ampere rating	Catalogue number	Max. no. 1-inch spaces	Max. no. 1/2-inch spaces	Cover Style	Dimensions (inches)			Wire size range for main Cu/Al
					H	W	D	
125	RCCPL102 <sup>b</sup>	2	4	Outdoor	11-1/2	6-1/2	4	#14–2/0
125	RCCPL104A <sup>b</sup>	4	8	Outdoor	11-1/2	6-1/2	4	#14–2/0
125	RCCPL108 <sup>b</sup>	8	16	Outdoor	13	11	3-1/2	#14–2/0

<sup>a</sup> Outdoor loadcentres accommodate Type DS conduit hubs. Hubs not included. See **page 15** for selection.

<sup>b</sup> All enclosures include a locking hasp as an integral part of the door latching mechanism.