




UPC Code : 78477225059

Country Of Origin : China

RoHS Compliant : Yes



## GUSB2-W

20A SmartlockPro® GFCI Combination 24W(4.8A) Type A USB In-Wall Charger Outlet

20 Amp, 125 Volt Receptacle/Outlet, 20 Amp Feed-Through, Tamper-Resistant, SmartlockPro® Self-Test GFCI Combination Type A USB In-Wall Charger, Wire Leads, NEMA 5-20R, 24W (4.8 Amps), Dual Type-A/A USB Chargers, screws and self-grounding clip included - White

- SAFE - Delivers continuous ground fault protection, automatically self-tests to ensure it can respond to a ground fault
- FAST CHARGING - Smart chip technology provides over 2X the charging power of other GFCI USB outlets for a faster charge
- CODE REQUIRED - Fulfill NEC® requirements anywhere GFCI protection is needed
- SIMPLE - Status indicator light provides simple, intuitive feedback
- INSTALL - Requires extra deep wallbox for installation

### Technical Information

#### Product Features

**Amperage** : 20 A  
**At Rated Voltage** : 1 HP  
**Brand** : SmartlockPro  
**Color** : White  
**Feature** : Self-Test  
**Flammability** : UL94, 5VA  
**Grade** : Residential/Commercial Specification Grade  
**Grounding** : Self-Grounding  
**Pole** : 2  
**Product Type** : GFCI/Outlet/USB Combo  
**Tamper Resistant** : Yes  
**Termination** : Wire leads (12AWG)  
**Trip Level** : Class A, 5mA plus or minus 1mA  
**Type** : GFCI/USB Combination  
**Voltage** : 125 VAC  
**Wallplate** : Not Included  
**Warranty** : 2-Year Limited  
**Wire** : 5

#### AC Horsepower Ratings

**At Rated Voltage** : 1 HP  
**Dielectric Voltage** : Withstands 1250VAC per UL 943 and CSA-C22.2 No. 144.1-06  
**Temperature Rise** : Max 30C after 100 cycles OL at 150 percent rated current

#### Electrical Specifications

**Grounding** : Self-Grounding  
**Ratings** : 20A - 125V, 4.8A @ 5V  
**Temperature Rise** : Max 30C after 100

**Operating Temperature** : -10°C to 40°C

#### Material Specifications

**Body Material** : Thermoplastic  
**Color** : White  
**Cover Material** : Thermoplastic  
**Face Material** : Thermoplastic  
**Grade** : Residential/Commercial Specification Grade  
**Line Contacts** : Brass Double Wipe .031 Thick  
**Notes** : Wallplate Not Included  
**Product ID** : Stamped on Strap  
**Strap Material** : Galvanized Steel  
**Terminal ID** : Green lead - GND. Line and load both have: Black lead - Hot, White lead - Neutral

#### Mechanical Specifications

**Pole** : 2  
**Tamper Resistant** : Yes  
**Type** : GFCI/USB Combination  
**Voltage** : 125 VAC  
**Wire** : 5

#### Standards & Certifications

**ANSI** : Yes  
**CSA C22.2 No. 42** : Yes  
**CSA-C22.2 No. 144.1-06** : Yes  
**FCC Part 15** : Class B  
**Fed Spec WC-596** : No  
**Listed** : cCSAus  
**NOM** : Yes  
**UL 1310** : Yes  
**UL 498** : Yes

cycles OL at 150 percent rated current

**Warranty** : 2-Year Limited

**Voltage** : 125 VAC

Environmental Specifications

**Flammability** : UL94, 5VA

### SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/>	
JOB NUMBER: <input type="text"/>	<input type="text"/>	<input type="text"/>

**Leviton Manufacturing Co., Inc.**

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):

+1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-

1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

Visit our Website at: [www.leviton.com](http://www.leviton.com)

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to:

[www.leviton.com/international/contacts/](http://www.leviton.com/international/contacts/)

