400-1400 series TIRE VALVES & TIRE HARDWARE

409

413 414 415

418 423 425

413-1 418-1

462 463

464 S 465

469 470 471

HI-PERFORMANCE TIRE VALVE

For use with mag, aluminum, exposed or reversed chrome wheels. Clamp-in type, brass chrome plated. Complete with two grommets to fit .453 or .625 valve holes.

409 / S 409 HI-PERFORMANCE TIRE VALVE

TUBELESS TIRE VALVES

Skin pack 2 per card	10/box	50/box	500/box	TR number	Rim hole diameter	Effective length inches
S 413	413-10	413-50	413-500	TR 413	.453”	1 1/4”
S 414	414-10	414-50	414-500	TR 414	.453”	1 1/2”
S 415	415-10	415-50	415-500	TR 415	.625”	1 1/4”
S 418	418-10	418-50	418-500	TR 418	.453”	2”
S 423	423-10	423-50	423-500	TR 423	.453”	2 1/2”
S 425	425-10	425-50	425-500	TR 425	.625”	2”

- Snap-in type
- Cap thread size: .305-32
- Ozone resistant rubber
- Maximum cold inflation pressure may not exceed: 60 PSI

CHROME SLEEVE TUBELESS TIRE VALVES

Chrome sleeve tubeless tire valve with hex cap. Fits .453 rim holes, replaces TR 413, TR-418.

413-1 / S 413-1 1 1/4” length, 10/box, 2/cd
418-1 2” length, 10/box

TRACTOR TIRE VALVES

462 TR-218A / ROAD GRADER & TRACTOR TUBES. Base prepared for electric or chemical application to tubes. Base 4 1/4”, length 1 27/32”. 5/box

463 TR-LN-10 / BRASS RIM NUT for air/water tractor valve

464 / S 464 TR-CH-3 / REPLACEMENT CORE HOUSING. Complete with valve core and cap for use with tractor valve. 10/box 2/cd

S 465 TR-CH-1 / REPLACEMENT CORE HOUSING. complete with valve core and cap for old style air/water valves. 2/cd

TUBLESS AIR-LIQUID VALVE

469 TR-618A / CLAMP-IN TUBELESS VALVE for farm tractor and road grader tires. Fast filling large bore type. Complete with 464 core housing. 2 1/2” length. 5/box

CLAMP-IN TUBELESS TIRE VALVES

470 UNIVERSAL CLAMP-IN. Rubber grommets fit 0.453” and 5/8” rim holes. Recommended when tire pressure exceeds 45 PSI. 5/box *(TR 416)*

471 SPECIAL CLAMP-IN. Recommended when tire pressure exceeds 45 PSI. 5/box *(TR 417)*

TUBE TYPE TIRE VALVES

For passenger car, motorcycle, light trucks, and industrial vehicles. Apply hot or cold. 2 1/4" base.

406 PLASTIC RIM HOLE REDUCER BUSHING FROM 5/8" TO .453" 100/box

473 PATCH VALVE. 1 3/8" for .453 rim hole Fits 13",14",15" tube. *(TR 13)* 5/box

406

TUBE TYPE TIRE VALVES

474 PATCH VALVE. 1 3/8" for .453 rim hole. Fits 16" tubes *(TR 15)* 5/box

475 PATCH VALVE. 3 1/2" Hand bendable for special applications *(TR 150)* 5/box

473
474

476 OVAL SLOT TUBELESS VALVE: Ready to use with grommet, washer, valve core, hex nut and screwdriver cap. For Firestone 16 x 6 KS wheel with oval valve hole. 5/box

475

476

TRUCK & BUS CLAMP-IN TUBELESS TIRE VALVES

Straight clamp-in type valves for 5/8" sidehole mounting. For demountable and non demountable rims.

481	3 17/32"	effective length *(TR 571)*	5/box
482	1 21/32"	effective length *(TR 501)*	5/box
483	2 5/32"	effective length *(TR 500)*	5/box
484	3 9/32"	effective length *(TR 570)*	5/box
485	3 29/32"	effective length *(TR 572)*	5/box
486	4 17/32"	effective length *(TR 573)*	5/box

481
482
483
484
485
486

TUBELESS VALVE

Used in drop center aluminum disc wheels with 5/8" bottom valve hole. *(TR 510)*

492 5/box

492

400-1400 series TIRE VALVES & TIRE HARDWARE

404

1455

434

435

436

437

439

1457

1458

440
440-1
440-2
440-3
440-4
440-5

VALVE CORES

404 VALVE CORE, 5/BAG
404-100 VALVE CORE, 5/BAG, 100/BOX
S 404 VALVE CORE, 5/CD

- Thread size: .2108-36, red teflon seal
- Operating temperature range: -40° to 302° F
- Operating pressure range: 0-200 PSI
- Meets specification TR- C1

1455 Large bore valve core *(TR-C2)*. Short type with .302-32 thread. 10/box

VALVE CAPS

434 Nickel plated, heavy knurl heat resistant sealing washer, 50/box

435 / S 435 Hex head, all brass, chrome plated, 50/box, 4/cd

436 / S 436 Dome type, brass, nickel plated, meets spec. TR VC3, 100/box, 5/cd

437 / S 437 Screw-driver type, brass, nickel plated, meets spec. TR VC2, 100/box, 5/cd

439 / S 439 Dome shape, plastic. TR VC8, 100/box, 5/cd
Standard valve caps: thread size: .305-32

1457 Large bore valve cap, hex head *(TR VC7)* 10/box

1458 Large bore valve cap screwdriver type *(TR VC6)* 10/box

TRUCK VALVE EXTENSIONS

Nickel plated brass, nickel plated long skirt, hi-heat cap, all thread sizes: .305-32.

440 1 3/8" effective length, 10/box
440-1 2 1/4" effective length, 10/box
440-2 3 1/16" effective length, 10/box
440-3 3 11/16" effective length, 10/box
440-4 4 1/8" effective length, 10/box
440-5 5 1/2" effective length, 10/box