



## IOS-CMP-U

- Zero crossing
- Adjustable time delay
- Adjustable ambient light sensor
- Suitable for use with electronic ballast
- Limited 2-year warranty

Model #	Voltage	Mounting Height	Coverage
IOS-CMP-U	120-277 VAC	8'	1,200 sq. ft.

### Rating:

**Voltage:** 120-277 VAC, 60 Hz.

**Adjustable Light Level:** 10fc - 150fc

**Adjustable Time Delay:** 15 sec. - 30 min.

**Coverage Pattern:** 360° 1200 sq. ft.

**Incandescent:** 800 W, 120 VAC 60 Hz.

**Inductive Ballast:** 800 VA, 120 VAC, 60 Hz. 1600 VA at 277 VAC, 60 Hz.

**Electronic Ballast:** 800 VA, 120 VAC, 60 Hz. 1600 VA at 277 VAC, 60 Hz.

**Motor:** ¼ HP, 120 VAC, 60 Hz.

**Operating Temperature:** 32°F to 131°F (0°C to 55°C)



Lens 2: 2,800 sq. ft.

## IOS-HB-U

- Zero crossing
- Adjustable time delay
- Adjustable ambient light sensor
- Suitable for use with electronic ballast
- Limited 2-year warranty

Model #	Voltage	Mounting Height	Coverage
IOS-HB-U	120-277 VAC	15'-50'	1200 sq. ft. (Lens 1) 2800 sq. ft. (Lens 2)

### Rating:

**Voltage:** 120-277 VAC, 60 Hz.

**Adjustable Light Level:** 10fc - 150fc

**Adjustable Time Delay:** 15 sec. - 30 min.

**Coverage Pattern:** (Lens 1) 360° 1200 sq. ft. (Lens 2) 360° 2800 sq. ft.

**Incandescent:** 800 W, 120 VAC, 60 Hz.

**Inductive Ballast:** 800 VA, 120 VAC, 60 Hz. 1600 VA at 277 VAC, 60 Hz.

**Electronic Ballast:** 800 VA, 120 VAC, 60 Hz. 1600 VA at 277 VAC, 60 Hz.

**Motor:** ¼ HP, 120 VAC, 60 Hz.

**Operating Temperature:** 32°F to 131°F (0°C to 55°C)



## IOS-CMP-LV

- Low Voltage remote mounted sensor
- Adjustable time delay
- Walk through detection
- Adjustable ambient light sensor
- Powered by IOS-PP24 power pack
- Limited 2-year warranty

Model #	Voltage	Mounting Height	Coverage
IOS-CMP-LV	24 VDC	8'	1,200 sq. ft.


### Rating:

**Voltage:** 24 VDC

**Adjustable Light Level:** 10fc - 150fc

**Adjustable Time Delay:** 15 sec. - 30 min.

**Operating Temperature:** 32°F to 131°F (0°C to 55°C)



## IOS-PP24

- Zero crossing
- Controls up to 6 IOS-CMP-LV
- Suitable for use with electronic ballast
- Multiple switching operations
- Limited 2-year warranty

Model #	Voltage
IOS-PP24	120-277 VAC

### Rating:

**Voltage:** 120-277 VAC, 50/60 Hz.

**Incandescent:** 15 A, 120 VAC, 50/60 Hz.

**Inductive Ballast:** 20 A, 120/240/277 VAC, 50/60 Hz.

**Motor:** 1 HP, 120/240 VAC, 50/60 Hz.

**Operating Temperature:** 32°F to 131°F (0°C to 55°C)