

SURGE SUPPRESSOR RC ELEMENT AC 127 TO 240V/DC 150 TO 250V FOR PLUGGING ONTO CONTACTORS WITHOUT/WITH AUX.CONTACT BLOCKS







General technical data:



<b>Product designation</b>		surge suppressor
<b>Design of the surge suppressor</b>		with RC elements

Control circuit/ Control:

<b>Type of voltage of the control supply voltage</b>		AC/DC
<b>Control supply voltage frequency</b>		
• 1 Rated value	Hz	50
• 2 Rated value	Hz	60
<b>Control supply voltage 1</b>		
• for DC		
— Initial rated value	V	150
— Final rated value	V	250
• with AC		
— at 50 Hz Initial rated value	V	127
— at 50 Hz Final rated value	V	240
— at 60 Hz Final rated value	V	240
— at 60 Hz Initial rated value	V	127

Certificates/ approvals:

General Product Approval			Test Certificates	Shipping Approval	
 CSA		 UR	<a href="#">Special Test Certificate</a>	 DNV	 GL

Shipping Approval	other				
 PRS	 RINA	<a href="#">Confirmation</a>	<a href="#">other</a>	<a href="#">Environmental Confirmations</a>	<a href="#">Declaration of Conformity</a>

### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/industrial-controls/catalogs>

**Industry Mall (Online ordering system)**

<http://www.siemens.com/industrymall>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TX44903T>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3TX44903T>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3TX44903T&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TX44903T&lang=en)

last modified:

27.04.2015