

Industrial grade AC toggle switches with CuVerro® antimicrobial copper surface


Product description

Single-pole, double-pole, 3-way, 4-way
15A, 120/277V/AC; 20A, 120/277V/AC

Toggle switches

Rating	A	V/AC	Description	Color suffix	Catalog no.	
20	120/277		Single-pole switch w/ CuVerro® toggle	CU, CUR	□ AH1221__	
20	120/277		Double-pole switch w/ CuVerro® toggle	CU, CUR	□ AH1222__	
20	120/277		3-Way switch w/ CuVerro® toggle	CU, CUR	□ AH1223__	
20	120/277		4-Way switch w/ CuVerro® toggle	CU, CUR	□ AH1224__	

Compliant with: cULus & FULS



AH1221


Industrial grade AC three-position switches

Product description

15A, 120/277V/AC; 20A, 120/277V/AC
Maintained & momentary contact
Single-pole, double-pole

AC maintained contact toggle switches, back & side wire


Rating	A	V/AC	Description	Color suffix	Catalog no.		
20	120/277		Single-pole, maintained contact toggle, center off	V	□ 2225V		
			Double-pole, maintained contact toggle, center off	B, V	□ 2226__		



1205

AC momentary contact switches, side wire


Rating	A	V/AC	Description	Color suffix	Catalog no.		
15	120/277		Single-pole, momentary contact toggle, center off	B, GY, V	□ 1895__		
			Single-pole, momentary contact locking, center off, nickel locking dome		□ 1895L		
20	120/277		Single-pole, momentary contact toggle, center off	B, GY, RD, V	□ 1995__		
			Single-pole, momentary contact toggle, center off	W	□ AH1995W		
			Single-pole, momentary contact locking, center off, nickel locking dome		□ 1995L		



1995

Accessories for industrial grade maintained & momentary switches

Description	Catalog no.		
Replacement key for locking switches, 1895L & 1995L	□ AH2000		
1-Gang, standard size, toggle, 302/304 Stainless steel wallplate	□ 93071		
1-Gang, standard size, toggle, unbreakable nylon wallplate	□ 5134V		



1995L



AH2000



93071



5134V

Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: B (Brown), GY (Gray), RD (Red), V (Ivory), W (White)

B	GY	RD	V	W
(Brown)	(Gray)	(Red)	(Ivory)	(White)

Specification information: 120/277V CuVerro® toggle switches: E-42, 120/277V Industrial maintained & momentary contact: E-34
Compliances and availability are subject to change without notice.

Indicates NAFTA compliant - Page Q-32

RoHS compliant - Page Q-32

Build-to-spec customizable devices - Page E-6