

## EMT

### Wet-location fittings



CI5620-WL



CI5612-IT-WL



CI5706-WL

#### Specifications

Material: Steel body and steel locknut

Finish: Electro zinc plated

Liner (insulated fittings only): Nylon

Threads: Hub threads (NPS)

Sealing gasket: Neoprene

Sealing ring: Nylon

Use: Wet locations, concrete-tight

UL Listed raintight (File E-16592)

UL514B / CSAC22.2-No.18.3

NEMA FB-1


NEMA 3R

#### Wet-location EMT compression fittings



Cat. no.	Hub size (in.)	Dimensions (in.)			Std. ctn.
		A	B	C	
<b>Non-insulated</b>					
CI5604-WL	½	1.22	0.47	1.14	100
CI5606-WL	¾	1.21	0.48	1.38	50
CI5608-WL	1	1.30	0.50	1.67	25
CI5610-WL	1¼	1.50	0.60	2.06	25
CI5612-WL	1½	1.53	0.65	2.27	20
CI5616-WL	2	1.67	0.73	2.77	10
CI5620-WL	2½	2.77	0.87	3.65	5
CI5624-WL	3	2.75	0.87	4.30	5
CI5632-WL	4	3.12	0.92	5.23	5
<b>Insulated</b>					
CI5604-IT-WL	½	1.22	0.54	1.14	100
CI5606-IT-WL	¾	1.21	0.55	1.38	50
CI5608-IT-WL	1	1.30	0.57	1.67	25
CI5610-IT-WL	1¼	1.50	0.69	2.06	25
CI5612-IT-WL	1½	1.53	0.74	2.27	20
CI5616-IT-WL	2	1.67	0.82	2.77	10
CI5620-IT-WL	2½	2.77	0.99	3.65	5
CI5624-IT-WL	3	2.75	0.99	4.30	5
CI5632-IT-WL	4	3.12	1.04	5.23	5

#### Diagrams



#### Wet-location EMT compression couplings



Cat. no.	Hub size (in.)	Dimensions (in.)		Std. ctn.
		A	B	
CI5704-WL	½	1.94	1.14	100
CI5706-WL	¾	2.09	1.38	50
CI5708-WL	1	2.31	1.67	25
CI5710-WL	1¼	2.58	2.06	25
CI5712-WL	1½	2.74	2.27	20
CI5716-WL	2	2.83	2.77	10
CI5720-WL	2½	4.47	3.65	5
CI5724-WL	3	4.70	4.30	5
CI5732-WL	4	5.75	5.23	5

#### Diagrams

