



Models

Product #	Volts (ph)	Watts	Weight		Product #	Volts (ph)	Watts	Weight	
			lbs	kg				lbs	kg
OAC02008	208 (1)	2000	24.0	10.9	OAC03007	347 (1)	3000	28.0	12.7
OAC04008	208 (1)	4000	24.0	10.9	OAC04007	347 (1)	4000	28.0	12.7
OAC04808	208 (1)	4800	24.0	10.9	OAC04807	347 (1)	4800	28.0	12.7
OAC08008	208 (1)	8000	50.0	22.7	OAC06007	347 (1)	6000	50.0	22.7
OAC12008	208 (1)	12000	90.0	40.9	OAC08007	347 (1)	8000	50.0	22.7
OAC12038	208 (3)	12000	90.0	40.9	OAC12007	347 (1)	12000	90.0	40.9
OAC01500	240/208 (1)	1500/1125	24.0	10.9	OAC01506	600 (1)	1500	28.0	12.7
OAC02000	240/208 (1)	2000/1500	24.0	10.9	OAC02006	600 (1)	2000	28.0	12.7
OAC03000	240/208 (1)	3000/2250	24.0	10.9	OAC03006	600 (1)	3000	28.0	12.7
OAC04000	240/208 (1)	4000/3000	24.0	10.9	OAC04006	600 (1)	4000	28.0	12.7
OAC04800	240/208 (1)	4800/3600	24.0	10.9	OAC04806	600 (1)	4800	28.0	12.7
OAC06000	240/208 (1)	6000/4500	50.0	22.7	OAC06006	600 (1)	6000	50.0	22.7
OAC08000	240/208 (1)	8000/6000	50.0	22.7	OAC08006	600 (1)	8000	50.0	22.7
OAC12000	240/208 (1)	12000/9000	90.0	40.9	OAC12006	600 (1)	12000	90.0	40.9
OAC01507	347 (1)	1500	28.0	12.7	OAC12036	600 (3)	12000	90.0	40.9
OAC02007	347 (1)	2000	28.0	12.7	-----	-----	-----	-----	-----

Add "BL" for white, "AM" for almond.

Accessories

Product #	Description	Length	
		in.	mm
OAC-BS1	Surface mounting box	1500W to 4800W	16 1/8 410
OAC-BS2	Surface mounting box	6000W to 8000W	32 3/8 822
OAC-BS3	Surface mounting box	12000W	48 13/16 1240

Control Options

Product #	Description
Product no-RT*	24V relay with transformer
Product no-R*	24V relay without transformer
OAC-DIS20*	Disconnect switch, 277V and less, double-pole, 20A
OAC-DIS40*	Disconnect switch, 600V max., three-pole, 40A
OAC-DIS80*	Disconnect switch, 600V, three-pole, 80A
OAC-IV*	Fan switch

* Factory installed

OAC series

Commercial Wall Heater

Cut down on cold drafts

The OAC heater provides a burst of heat in areas affected by cold drafts. Designed for residential, commercial and industrial use, the unit can be recessed or surface-mounted.

Powered by a closed factory-lubricated motor, the fan blows warm air downward to create air circulation.



apartment building

commercial building

entrance way

stairwell

garage



Features

- Color**
 - Standard: white, almond.
 - Optional and custom colors available upon request.
- Finish**
 - Standard: epoxy/polyester powder paint.
- Voltage**
 - 208V, 240V/208V, 277V, 347V, 480V, 600V, 1 or 3-phase.
- Construction**
 - 18-gauge steel louvres; grille with rounded corners*.
 - Bottom air outlet.
 - High-limit temperature control with automatic reset.
- Fan**
 - Closed, factory-lubricated motor.
 - 160 cfm fan (1.5 to 4.8 kW; 55 dBA);
 - 2 X 160 cfm fan (6 to 8 kW; 58 dBA);
 - 3 X 160 cfm fan (12 kW; 61 dBA).
 - Fan delay purges heater of residual heat.
 - (Any remote thermostat or relay must be connected to the heater control terminal block)
- Heating element**
 - Durable tubular heating element with fins.
- Control**
 - Built-in thermostat included, 0-50 °C (32-120 °F).
 - Combination with knob or tamperproof (hidden).
 - Note: Thermostat is not installed in heater with factory installed relay.*
- Installation**
 - Standard 60 °C (140 °F) wiring is sufficient.
 - Adaptor for surface mounting available.
 - Minimum clearance from the floor and adjacent walls: 10 in. (25.4 cm).
- Warranty**
 - 1-year warranty against defects.

* The grilles with rounded corners may be installed on existing units.