


# SHOE BOX & WALL PACK RETROFITS G4 HORIZONTAL MOUNTING



VOLTAGE\*\*



MEDIUM + MOGUL BASES



INSTALL METHOD



OPERATING TEMP



ACTIVE COOLING



SURGE PROTECTION



CRI



RATED LIFE



WARRANTY

## directional efficiency



LED-8089M


- 50W, 80W and 110W models replacing up to 400W HID
- Light panel can rotate once the base is tightened to direct light out of the fixture
- Includes a fan and thermal sensor to run cool and ensure a long and bright life
- Enclosed fixture safe and approved for damp locations
- USA designed and specified driver
- Available in 3000, 4000 and 5000K

includes support feet to prevent socket sag\*

\*LED-8089 and 8090 only



LED-8090M offers choice of optics



PART #	UPC	REPLACES	WATTAGE	LUMENS	CCT (K)*	BASE	OPTICS	DLC PRODUCT CODE
LED-8088E50-G4	844006083427	up to 175W HID	50W	6250	5000K	E26	TYPE V	PXNCL1EK
LED-8088M50-G4	844006083472	up to 175W HID	50W	6250	5000K	EX39	TYPE V	PL1EIQY3
<b>LED-8089M50-G4</b>	<b>844006083526</b>	<b>up to 250W HID</b>	<b>80W</b>	<b>10000</b>	<b>5000K</b>	<b>EX39</b>	<b>TYPE V</b>	<b>PMK0Q4Q6</b>
LED-8090M50-G4	844006083571	up to 400W HID	110W	13750	5000K	EX39	TYPE V	PDL12RJC
LED-8090M50-G4-T3	844006083915	up to 400W HID	110W	12840	5000K	EX39	TYPE III	PZF9RH41
LED-8090M50-G4-T4	844006083922	up to 400W HID	110W	12780	5000K	EX39	TYPE IV	PDOOZLSD

\* See page 2 for additional color temperatures.


\*\* See page 2 for 347 volt options for Canada. 🇨🇦




# SHOE BOX & WALL PACK RETROFITS G4 HORIZONTAL MOUNTING




LED-8088E




LED-8088M



LED-8089M



LED-8090M



LED-8088 RECOMMENDED MINIMUM FIXTURE SIZE  
5.4" w x 11.9" h / 347 cu. in. volume

LED-8089/LED-8090 RECOMMENDED MINIMUM FIXTURE SIZE  
6" w x 12" h / 432 cu. in. volume

## ORDERING GUIDE

PART #	UPC	REPLACES	WATTAGE	LUMENS	CCT (K)	BASE	OPTICS	DLC PRODUCT CODE
LED-8088E30-G4	844006083380	UP TO 175W HID	50W	5750	3000K	E26	TYPE V	N/A
LED-8088E40-G4	844006083403	UP TO 175W HID	50W	6250	4000K	E26	TYPE V	N/A
LED-8088E50-G4	844006083427	UP TO 175W HID	50W	6250	5000K	E26	TYPE V	N/A
LED-8088M30-G4	844006083434	UP TO 175W HID	50W	5750	3000K	EX39	TYPE V	PRZY4XA1
LED-8088M40-G4	844006083458	UP TO 175W HID	50W	6250	4000K	EX39	TYPE V	PXNCL1EK
LED-8088M50-G4	844006083472	UP TO 175W HID	50W	6250	5000K	EX39	TYPE V	PL1EIQY3
LED-8089M30-G4	844006083489	UP TO 250W HID	80W	9200	3000K	EX39	TYPE V	POVBC5FD
LED-8089M40-G4	844006083502	UP TO 250W HID	80W	10000	4000K	EX39	TYPE V	P6X6TWU7
LED-8089M50-G4	844006083526	UP TO 250W HID	80W	10000	5000K	EX39	TYPE V	PMK0Q4Q6
LED-8090M30-G4	844006083533	UP TO 400W HID	110W	12650	3000K	EX39	TYPE V	P4A1ACGH
LED-8090M40-G4	844006083557	UP TO 400W HID	110W	13750	4000K	EX39	TYPE V	P2TFM5JG
LED-8090M50-G4	844006083571	UP TO 400W HID	110W	13750	5000K	EX39	TYPE V	PDL12RJC
LED-8090M40-G4-T3	844006083892	UP TO 400W HID	110W	12630	4000K	EX39	TYPE III	PSPXBHZ5
LED-8090M40-G4-T4	844006083908	UP TO 400W HID	110W	12165	4000K	EX39	TYPE IV	PA18YDOM
LED-8090M50-G4-T3	844006083915	UP TO 400W HID	110W	12840	5000K	EX39	TYPE III	PZF9RH41
LED-8090M50-G4-T4	844006083922	UP TO 400W HID	110W	12780	5000K	EX39	TYPE IV	PDO0ZLSD

## 347 VOLT OPTIONS FOR CANADA

PART #	UPC	REPLACES	WATTAGE	LUMENS	CCT (K)	BASE	OPTICS	DLC PRODUCT CODE
LED-8088E40C-G4	844006083397	175W HID	50W	6460	4000K	E26	TYPE V	N/A
LED-8088E50C-G4	844006083410	175W HID	50W	7250	5000K	E26	TYPE V	N/A
LED-8088M40C-G4	844006083441	175W HID	50W	6460	4000K	EX39	TYPE V	PMYAWNDV
LED-8088M50C-G4	844006083465	175W HID	50W	7250	5000K	EX39	TYPE V	PGF6Y2D5
LED-8089M40C-G4	844006083496	250W HID	80W	12010	4000K	EX39	TYPE V	PQK2CH2K
LED-8089M50C-G4	844006083519	250W HID	80W	11655	5000K	EX39	TYPE V	PMDHOX9W
LED-8090M40C-G4	844006083540	400W HID	110W	15430	4000K	EX39	TYPE V	N/A
LED-8090M50C-G4	844006083564	400W HID	110W	14570	5000K	EX39	TYPE V	N/A
LED-8090M40C-G4-T3	844006083939	400W HID	110W	12630	4000K	EX39	TYPE III	P7OWSLYH
LED-8090M40C-G4-T4	844006083946	400W HID	110W	12165	4000K	EX39	TYPE IV	PQ1BR41U
LED-8090M50C-G4-T3	844006083953	400W HID	110W	12840	5000K	EX39	TYPE III	P929E8A1
LED-8090M50C-G4-T4	844006083960	400W HID	110W	12780	5000K	EX39	TYPE IV	PFCVP0WP

