

DEEP WELL IMPACT SOCKETS



Chromoly Steel & Custom Heat Treat
Maximum Durability in High Torque Applications



Radius Corners
Drives on Flats to Reduce Stripping & Breakage



Thin Wall Construction
Impact Strength in Tight Clearance Applications

Size	3/8" Drive 1 Pack	1/2" Drive 1 Pack
5/16"	49-66-4422	-
3/8"	49-66-4424	49-66-4461
7/16"	49-66-4425	49-66-4462
1/2"	49-66-4426	49-66-4463
9/16"	49-66-4427	49-66-4464
5/8"	49-66-4428	49-66-4465
11/16"	49-66-4429	49-66-4466
3/4"	49-66-4430	49-66-4467
13/16"	49-66-4431	49-66-4468
7/8"	49-66-4432	49-66-4469
1"	-	49-66-4471
1-1/16"	-	49-66-4472
1-1/8"	-	49-66-4473
1-1/4"	-	49-66-4475



ADAPTERS INCLUDING EXPAND

Bit Length	Size	1 Pack	3 Pack	Bulk 10 Pack
Insert	1/4" Hex to 1/4" Socket	48-32-5020	-	-
	1/4" Hex to 3/8" Socket	48-32-5021	-	-
	1/4" Hex to 1/2" Socket	48-32-5022	-	-
	3 Pc Socket Adapters (1/4", 3/8", 1/2")	-	48-32-5023	-
1-7/8"	1/4" Hex to 1/4" Socket	48-32-5030	-	48-32-5730
	1/4" Hex to 3/8" Socket	48-32-5031	-	48-32-5731
	1/4" Hex to 1/2" Socket	48-32-5032	-	48-32-5732
	3/8" Socket to 1/4" Hex	48-03-4405	-	-
	1/2" Socket to 1/4" Hex	48-03-4410	-	-
	3 Pc Socket Adapters (1/4", 3/8", 1/2")	-	48-32-5033	-



DEEP WELL IMPACT SOCKET SETS



Product No.	49-66-4301	49-66-4419	49-66-4484	49-66-4417
Description	12 Pc Deep Well Impact Socket Set	8 Pc Deep Well Impact Socket Set	9 Pc Deep Well Impact Socket Set	3 Pc Thin Wall Deep Impact Socket Set
Drive	1/4"	3/8"	1/2"	3/8"
Measurement Standard	Metric	SAE	SAE	SAE
Contents	5.5mm, 6mm, 7mm, 8mm, 9mm, 10mm, 11mm, 12mm, 13mm, 14mm, 15mm, 1/4" Hex to 1/4" Square Adapter	5/16", 3/8", 7/16", 1/2", 9/16", 5/8", 11/16", 3/4"	3/8", 7/16", 1/2", 9/16", 5/8", 11/16", 3/4", 7/8", 1/4" Hex to 1/2" Square Adapter	1/2", 9/16", 1/4" Hex to 3/8" Square Adapter

ADAPTERS



30° Off-Set Drive Adapter



Right Angle Drive Attachment

Description	Part Number
30° Off-Set Drive Adapter	48-32-2100
Right Angle Drive Attachment	49-22-8510
1/2" Square to 7/16" Hex Quick Change Impact Adapter	48-66-0061