

HEAVY DUTY TOGGLES



Fig. 1



Fig. 2



Fig. 3



Fig. 4



Fig. 5



Fig. 6

Retail Part No.	Bulk Part No.	Figure No.	Circuit Function			Poles/Throws	AMPS 125VAC	AMPS 250VAC	HP 125-250VAC	Actuator Style	Actuator Material	Bushing Length	Mounting Hole	Terminal Type	Hardware	Spec. Drawing Page No.
35-110	35-110-BU	3	On	Off	On	SPDT	20	10*	3/4	Bat	Metal	0.470"	0.500"	Screw	N, KN, Sc	H-15 A
35-130	35-130-BU	3	On		On	SPDT	20	10*	3/4	Bat	Metal	0.470"	0.500"	Screw	N, KN, Sc	H-15 A
35-148	35-148-BU	3	On	Off	On	DPDT	20	10*	1-1/2	Bat	Metal	0.470"	0.500"	Screw	N, KN, Sc	H-15 B
35-155	35-155-BU	5	(On)	Off	(On)	SPDT	20	10*	3/4	Bat	Brass	0.325"	0.500"	Screw	N, KN, Sc	H-15 A
35-156	35-156-BU	4	On		(On)	DPDT	20	10	1-1/2	Bat	Brass	0.468"	0.500"	QC .250"	N, KN	H-15 D
35-185	35-185-BU	2	On		Off	DPST	20	10*	1-1/2	Bat	Metal	0.465"	0.500"	QC .250"	N, KN	H-15 C
35-3005	35-3005-BU	6	On		Off	SPST	20	10	3/4	Bat	Brass	0.325"	0.500"	QC .250"	N, KN	H-15 E
35-3010	35-3010-BU	6	On		On	SPDT	20	10	3/4	Bat	Brass	0.325"	0.500"	QC .250"	N, KN	H-15 E
35-3020	35-3020-BU	4	On		On	DPDT	20	10*	1-1/2	Bat	Brass	0.468"	0.500"	QC .250"	N, KN	H-15 D
35-3060	35-3060-BU	2	On		Off	DPST	20	10*	1-1/2	Bat	Brass	0.468"	0.500"	Screw	N, KN, Sc	H-15 F

Notes: (On)/(Off) = Momentary On/Off
 *Rated @ 277VAC
 **1&2 On
 ***Rated 35A @ 6VDC/20A @ 12VDC
 FN = Face Nut
 † = Progressive Two Circuit

ID = ID Plate
 KN = Knurled Nut
 N = Nut
 QC = Quick Connect
 Sc = Screw

Note: All figures are for illustration purpose only, and the number/type of terminals may vary.

All quantities are single; BU's are packages of 25 Unless otherwise noted.