

CIRCUIT BREAKERS

Retail Part No.	Bulk Part No.	Figure No.	Amps 125/250 VAC/32VDC	Actuator	Mounting Hole	Hardware	Spec. Drawing Page No.
35-2103	35-2103-BU	1	3	Black Plastic Button	0.450"	Nut, Knurling Nut; ID Plate	H-43 A
35-2104	35-2104-BU	1	4	Black Plastic Button	0.450"	Nut, Knurling Nut; ID Plate	H-43 A
35-2105	35-2105-BU	1	5	Black Plastic Button	0.450"	Nut, Knurling Nut; ID Plate	H-43 A
35-2106	35-2106-BU	1	6	Black Plastic Button	0.450"	Nut, Knurling Nut; ID Plate	H-43 A
35-2107	35-2107-BU	1	7	Black Plastic Button	0.450"	Nut, Knurling Nut; ID Plate	H-43 A
35-2108	35-2108-BU	1	8	Black Plastic Button	0.450"	Nut, Knurling Nut; ID Plate	H-43 A
35-2110	35-2110-BU	1	10	Black Plastic Button	0.450"	Nut, Knurling Nut; ID Plate	H-43 A
35-2112	35-2112-BU	1	12	Black Plastic Button	0.450"	Nut, Knurling Nut; ID Plate	H-43 A
35-2115	35-2115-BU	1	15	Black Plastic Button	0.450"	Nut, Knurling Nut; ID Plate	H-43 A
35-2120	35-2120-BU	1	20	Black Plastic Button	0.450"	Nut, Knurling Nut; ID Plate	H-43 A
35-2125	35-2125-BU	1	25	Black Plastic Button	0.450"	Nut, Knurling Nut; ID Plate	H-43 A
35-2130	35-2130-BU	1	30	Black Plastic Button	0.450"	Nut, Knurling Nut; ID Plate	H-43 A
35-2135	35-2135-BU	1	35	Black Plastic Button	0.450"	Nut, Knurling Nut; ID Plate	H-43 A
35-2140	35-2140-BU	1	40	Black Plastic Button	0.450"	Nut, Knurling Nut; ID Plate	H-43 A



Fig. 1

SPECIALTY SWITCHES



Fig. 2



Fig. 3



Fig. 4



Fig. 5



Fig. 6



Fig. 7



Fig. 8



Fig. 9



Fig. 10



Fig. 11

Retail Part No.	Bulk Part No.	Figure No.	Circuit Function	Poles & Throws	Amps 125 VAC	Amps 250 VAC	Actuator	Terminal Style	Body Color	Spec. Drawing Page No.
35-864	35-864-BU	2	On Off	SPST	6	3	3-1/2" Pull Chain	6" Wire Leads		H-43 B
35-865	35-865-BU	3	Off 1-On 2-On	SPDT^	6	3	3-15/16" Pull Chain	Push-in	Purple	H-43 C
35-867	35-867-BU	3	Off 1-On 2-On 3-On	SP3T	6	3	3-3/4" Pull Chain	Push-in	White	H-43 D
35-849	35-849-BU	4	On Off	SPST	6	3	Thumbwheel	Insulation Piercing	White Plastic	H-43 E
35-853	35-853-BU	4	On Off	SPST	6	3	Thumbwheel	Insulation Piercing	Black Plastic	H-43 E
35-1851	35-1851-BU	5	On Off	SPST	6*		Rocker	Solder	Black Plastic	H-43 F

Retail Part No.	Bulk Part No.	Figure No.	Action	Poles & Throws	Amps 20 VAC/DC	Amps 120 VAC	Amps 80 VDC	Actuator	Terminal Type	Mounting Type	Gap	Spec. Drawing Page No.
35-750	35-750-BU	7	NO w/o Magnet	SPST	0.5**	0.08	0.10	Magnet Incl.	Screw	Surface	0.250"	H-43 H
35-756	35-756-BU	7	NO or NC	SPDT	0.015	0.025	0.0375	Magnet Incl.	Screw	Surface	0.250"	H-43 H

Retail Part No.	Bulk Part No.	Figure No.	Action	Poles & Throws	Amps 30 VAC	Amps 120 VAC	Watts 30 VDC	Actuator	Terminal Type	Mounting Type	Gap	Spec. Drawing Page No.
35-754		8	NO w/o magnet	SPST	0.3		3	Magnet Incl.	Side WL	Submin. Surface	1.000"	H-43 I
35-762		9	NO w/o magnet	SPST	0.3		3	Magnet Incl.	WL	Recessed, 3/8" dia.	1.250"	H-43 J

Retail Part No.	Bulk Part No.	Figure No.	Action	Poles & Throws	Amps 6 VDC	Amps 125 VAC	Tilt Angle	Actuator	Terminal Type	Mounting Type	Mounting Holes	Spec. Drawing Page No.
35-730	35-730-BU	10	On Off On	DPDT	1/2			Plastic Handle	Screw		3.40 mm	H-43 K
35-764	35-764-BU	11	NO or NC	SPST		1/2	15°	Int. Metal Ball	Leads			H-43 L

Notes: *Rated 6Amps@120VAC
 **10 Watts Max.
 Sd = Solder

^ = 3 Position
 Incl. = Included

WL = Wire Lead(s)
 † = 0.2 Amps@120VDC Max., 4 Watts max.

Int. = Internal

***Rated 0.01A 120VAC, 450mA 1.5VDC, 20mA 50VDC
 NO/NC = Normally Open or Normally Closed
 †† = Ampere turns = 15-90

All quantities are single; BU's are packages of 25 Unless otherwise noted.