



LT Series

Power-Free “Exit”, “Sortie” or Pictogram Exit Sign

Type: _____
 Project/Location: _____
 Contractor: _____
 Prepared By: _____
 Date: _____
 Model No.: _____

FEATURES

- Illumination provided by borosilicate glass tubes, internally coated with zinc sulphide phosphor and filled with tritium gas
- Minimum brightness at time of manufacture is 0.132 foot-lambert (0.452 cd/m²)
- Decorative, slim-line heavy-duty ABS housing
- Rugged, impact-resistant polycarbonate face
- Spark-free construction
- Simple installation – universal direction capability, comes complete with universal mounting hardware
- Stands up to extreme temperatures in outdoor or indoor applications
- Life expectancy of 10 or 20-year (EXIT), 12-year (SORTIE) and 10-year (Pictogram)
- Available in single or double face
- Certified to standard UL924 (ULC-S572)
- Pictogram Sign includes universal stencils (straight from here, left from here and right from here)



TYPICAL SPECIFICATIONS

Supply and install Lumacell® LTEU (EXIT) or LTSU (SORTIE) or LT (Pictogram) Series Self-Luminous Exit Signs. The Exit Sign shall be constructed of a thermoplastic housing and be corrosion proof. The sealed housing will incorporate no loose or removable parts allowing for easy installation.

The standard minimum guaranteed life will be 10 years. The standard mounting brackets will allow for either end/ceiling or wall mount. Standard “Exit” and “Sortie” Signs shall be supplied with white letters that are 6” high by 3/4” stroke. The initial average minimum brightness shall be 0.132 foot-lambert (0.452 cd/m²).


The equipment shall be Lumacell® Model: _____ .

WIRE GUARDS

460.0079-L	Wall Mount
460.0027-L	End Mount
460.0028-L	Ceiling Mount

DIMENSIONS

Dimensions are approximate and subject to change.



ORDERING INFORMATION: EXIT OR SORTIE SIGN

SERIES	BACKGROUND COLOURS	HOUSING COLOURS	LIFE YEARS	OPTIONS	NEW
LTEU1= EXIT sign, single face, universal mount and chevrons LTEU2= EXIT sign, double face, universal mount and chevrons LTSU1= SORTIE sign, single face, universal mount and chevrons LTSU2= SORTIE sign, double face, universal mount and chevrons	Blank= red	Blank= grey* B= black WH= white*	10= 10 years (EXIT) 12= 12 years (SORTIE) 20= 20 years (EXIT)	-AF= aluminium frame -PC= polycarbonate shield -VR= vandal cover	-N
* Not available in Sortie					

EXAMPLE: LTEU110-AF-N

ORDERING INFORMATION: PICTOGRAM SIGN

SERIES	FACEPLATES AND MOUNTING	HOUSING COLOURS	LIFE YEARS	OPTIONS
LT= Pictogram Exit Sign	1= single face universal mount and chevrons 2= double face universal mount and chevrons	B= black G= grey W= white	10= 10 years	AF= Aluminium frame PC= Polycarbonate shield VR= Vandal cover

EXAMPLE: LT1W10AF

Unlike Exit or Sortie, the Pictogram Sign is not available in double arrow configuration.