

FIRESTOP BLOCK CFS-BL

Product description

- Ready-to-use, intumescent flexible block designed to seal medium to large size openings

Applications for use

- Temporary or permanent sealing of cables, cable trays and pipes in wall and floor openings
- Sealing single or multiple penetrations in small to large openings
- Temporary or permanent sealing of insulated and non-insulated metallic pipes and combustible pipe penetrations

Advantages

- Integrated “Grid-Tech” increases Annular Space up to 12” with no wire mesh
- Suitable for re-penetration or new penetrations
- Economical to use with short installation times
- Easy installation — no special tools required
- Ideal for use in floors — no forming required
- One sided wall systems available
- Halogen, asbestos and solvent free
- Operational immediately after installation
- Smoke resistant
- Completely dust and fiber free for “clean room” installation

Installation instructions

- See Hilti literature or third-party listings for complete application and installation details



Technical Data

Chemical basis	Polyurethane Foam
Color	Red
Recommended application temperature	40° F to 104° F (5° C to 40° C)
Storage and transportation temperature range	32° F to 140° F (0° C to 60° C)
Temperature resistance range	5° F to 140° F (-15° C to 60° C)
Density	0.27 g/cm ³
Mold and mildew performance	Class 0 (ASTM G21-96)
Tested in accordance with	UL 1479, CAN/ULC-S115, ASTM E814
Surface burning characteristics (ASTM E84)	Flame Spread 10 Smoke Development 15
Intumescent activation	392° F (200° C)
LEED VOC	5.4 g/L
Can be painted	Yes
Acoustics performance	52 (relates to specific construction) ASTM E90
Shelf life	Unlimited
Expansion ratio	1:3

Order designation	Sales pack quantity	Item number
CFS-BL Firestop Block	1	2030020
CFS-BL MC	20	3484119
CFS-BL Pallet	480	3541548

Dimensions	Size (LxWxH)
CFS-BL Firestop Block	8" x 5" x 2" (20x13x5cm)

