



## Watertight Devices

## Heavy-Duty Portable Outlet Boxes and Plates

## Heavy-Duty Portable Outlet Boxes and Cover Plates

Description	Catalog Number
Box with cord strain relief, with one blank cover plate.	HBLPOB1
Box with cord strain relief, with one blank cover plate, black.	HBLPOB1BK
Box with cord strain relief, with two duplex (indoor) cover plates.	HBLPOB1D
Box with cord strain relief, with two duplex (indoor), yellow cover plates.	HBLPOB1DY
Blank, non-metallic FS cover plate with foam gasket, gray.	HBLP14FS
Duplex, non-metallic FS cover plate, gray.	HBLP8FS
Duplex, non-metallic FS cover plate, yellow.	HBLP8FSY
Single receptacle (1.39"), non-metallic FS cover plate, gray.	HBLP7FS
Single receptacle (1.56"), non-metallic FS cover plate, gray.	HBLP720FS
Rectangular opening, non-metallic FS cover plate, gray.	HBLP26FS



HBLPOB1

## Other Cover Plates and Devices

## which may be used with Heavy-Duty Portable Outlet Boxes

Description	Catalog Number
Duplex cover plate, weatherproof.	HBL5221, HBL52CM21
Single receptacle (1.39") cover plate, weatherproof.	HBL7423WO, HBL74CM23WO
Single receptacle (1.56") cover plate, weatherproof.	HBL7425WOA, HBL74CM25WOA
Safety-Shroud Twist-Lock® surface receptacles.	HBL2310SR series, HBL2410SR series

Note: Standard product gray, CM yellow.



Cover Plates

## Deluxe Cord Grips Straight Male Thread

## Nylon Fittings, Stainless Steel Mesh, Liquidtight, for Insulated Cables

Grip Diameter Inches	Range (cm.)	Thread Size N.P.T. (inches)	Form Size	Catalog Number
.375"-.500"	(.95-1.27)	3/4"	F3	074011335
.500"-.625"	(1.27-1.59)	3/4"	F3	074011336
.625"-.750"	(1.59-1.90)	3/4"	F3	074011337

## Nylon Cord Connector Straight Male Thread


Grip Diameter Inches	Range (cm.)	Thread Size N.P.T. (inches)	Form Size	Catalog Number
.375"-.500"	(.95-1.27)	3/4"	F3	SHC1035CR
.500"-.625"	(1.27-1.59)	3/4"	F3	SHC1036CR
.625"-.750"	(1.59-1.90)	3/4"	F3	SHC1037CR

## Specifications for Heavy-Duty Portable Outlet Boxes and Cover Plates

UL Listed	UL 514C, UL467 and UL50 Enclosures Types 1, 3R.
CSA Certified	C22.2 No. 18 and C22.2 No. 94 Enclosures Types 1, 3R and C22.2 No. 0.4 (Impedance).
Box Specifications:	
Moisture Resistance	Wet and damp locations, Enclosure Type 3R when used with weatherproof cover plates. Dry, indoors locations, Enclosure Type 1 with all other cover plates.
Flammability	UL 94V-0, 94-5VA classification.
Operating Temperature	80°C maximum; -35°C minimum.
UV Resistance	All materials are UV stabilized.
Impact and Crush Resistance	in accordance with UL 514C, UL50, C22.2 No. 18 and C22.2 No. 94.
Material	Valox®.
Cord Connector Materials	Nylon nut; Nylon Gotcha® ring; Neoprene grommet.
Cord Diameter Range	.38" to .75" diameter.
Bonding Strap Material	Brass.
Threaded Inserts	Brass.
Grounding Screw Material	Brass.
Indoor Cover Plate Screws Material	Zinc Plated Steel.
Outdoor Cover Plate Screws Material	Stainless Steel.
Cover Plate Gasket Material	UL recognized closed-cell foam (aging and oil resistant).

Deluxe Cord Grips  
(purchased separately)Gray Nylon  
Cord Connector

## Dimensions Inches (mm)



HBLPOB1

Valox® is a trademark of SABIC Innovative Plastics, acquired from General Electric Company.