





**UPC Code:** 07847781979

Country Of Origin: United States



# **BR20**

Duplex Receptacle Outlet, Commercial Specification Grade, Indented Face, 20 Amp, 125 Volt, Back or Side Wire, NEMA 5-20R, 2-Pole, 3-Wire, Self-Grounding - Brown

#### **Technical Information**

AC Horsepower Ratings
At Rated Voltage: 1 HP

Electrical Specifications

Amperage: 20 A

**Current Limiting:** Full Rated Current **Dielectric Voltage:** Withstands 2000V

per UL498

**Grounding:** Self-Grounding

Pole: 2

Temperature Rise: Max 30C after 100 cycles OL at 150 percent rated current

Voltage: 125 VAC

Wire: 3

**Environmental Specifications** 

Operating Temperature: -40°C to 60°C

Material Specifications

Body Material: Polypropylene

Clamp Nuts: Brass Color: Brown

Face Material: Polypropylene

**Ground Clips:** Brass

Grounding Screw: Brass 8-32

Line Contacts: Brass Triple-Wipe .031

Thick

Strap Material: Zinc-Plated Steel Terminal Screws: Brass 8-32

## Mechanical Specifications

Product ID: Ratings are permanently

marked on device

Terminal Accom.: 14-10 AWG

Terminal ID: Brass-Hot, Green-Ground,

Silver-Neutral

Termination: Back or Side Wire

Product Features
Color: Brown

Device Type: Duplex Receptacle Outlet

Feature 4: Indented Face

Grade: Commercial Specification Grade

**NEMA:** 5-20R

Standards and Certifications

**ANSI:** C-73

CSA C22.2 No. 42: File 152105

**NEMA:** WD-1 & WD-6

**NOM:** 057

**UL498:** File E13399 **Warranty:** 10 Year Limited

CDECIFICATION	CLIDMITTAL
SPECIFICATION	SUBMITTAL

or gon for more committee		
I	JOB NAME:	CATALOG NUMBERS:
ı		
	JOB NUMBER:	

## Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920  $\cdot$  FAX: +1-800-832-9538  $\cdot$  Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

## Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

## Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

## Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

## Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

