




Color: White

UPC Code: 07847738179 Country Of Origin: Mexico



T5015-W

Single Receptacle Outlet, Commercial Specification Grade, Tamper-Resistant, Smooth Face, 15 Amp, 125 Volt, Side Wire, NEMA 5-15R, 2-Pole, 3-Wire, Self-Grounding - White

Technical Information

AC Horsepower Ratings At Rated Voltage: 1/2 HP

Electrical Specifications

Grounding: Self-Grounding Amperage: 15 A

Voltage: 125 VAC

Pole: 2

Wire: 3

Dielectric Voltage: Withstands 2000V per UL498

Current Limiting: Full Rated Current Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

Environmental Specifications Flammability: Rated V-2 per UL94 Operating Temperature: -40°C to 60°C

Material Specifications


Face Material: Thermoplastic Nylon Body Material: Thermoplastic Nylon Line Contacts: Brass Triple-Wipe Terminal Screws: Brass 10-32 Grounding Screw: Brass 8-32 Strap Material: Zinc-Plated Steel Clamp Nuts: Zinc-Plated Steel Ground Clips: Brass-Plated Color: White Mechanical Specifications Terminal ID: Brass-Hot, Green-Ground, Silver-Neutral Terminal Accom.: 14-10 AWG Product ID: Ratings are permanently marked on device Termination: Side Wire

Product Features NEMA: 5-15R Color: White Device Type: Single Receptacle Outlet Feature 2: Tamper-Resistant Feature 4: Smooth Face Grade: Commercial Specification Grade


Standards and Certifications

NEMA: WD-6 ANSI: C-73 UL498: File E13399 UL Fed Spec WC-596: File E13399 CSA C22.2 No. 42: File 152105 NOM: 057 Warranty: 10 Year Limited

Dimensional Diagram



Wiring Diagram



5-15R

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747 Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

