



Color: White

UPC Code: 06867918075

# 5693-CW

Decora Plus 3-Way Rocker Switch, Commercial Specification Grade, Canadian, 15 Amp, 347 Volt AC, Back or Side Wire, Self-Grounding - White

### **Technical Information**

Electrical Specifications

Amperage: 15 A

Dielectric Voltage: Withstands 1500V

for 1 minute

Endurance: 50,000 cycles minimum

Overload UL20 Test: 100 cycles of OL

at 4.8 times rated current

Temperature Rise: Maximum 30

degrees C rise
Voltage: 347 VAC

**Grounding:** Self-Grounding

Environmental Specifications

Flammability: Rated V-2 per UL 94

Operating Temperature: -40°C to 65°C

Material Specifications

Actuator Material: Thermoplastic Body Material: Thermoplastic

Color: White

Strap Material: Steel

Mechanical Specifications

Grounding: Self-Grounding

Product ID: Stamped on Strap

**Terminal Accom.:** 14-#10 AWG back wired; #14-#12 AWG side wired

Terminal ID: Brass-Hot (If Applicable) Black-Hot White-Neutral Green-Gnd Termination: Back or Side Wire

Torque Range: 12-14 inch pounds

Product Features

Brand: Decora Plus

Feature 4: Canadian

Function: 3-Way

Grade: Commercial Specification Grade

Device Type: Rocker Switch

Color: White Voltage: 347 VAC

## SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

### Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):

+1-800-824-3005

# Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

### Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

#### Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

# Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

