



Product Description

Security & Sound Cable, Riser-CMR, 4-18 AWG stranded bare copper conductors with polypropylene insulation, Beldfoil® shield and PVC jacket with ripcord

Technical Specifications

Product Overview

Suitable Appli	cations:		Security S	tem, Intercom/PA, Audio/Speaker, P	ower-Limited Controls,	, Noisy Environment	
Constructi	on Details						
Jonistraoti	on Betano						
Conductor							
Element	Number of Element	Size	Stranding	Material			
Conductor(s)	4	18 AWG	7x26	BC - Bare Copper			
Insulation							
Element	Material	Nom. Th	ickness	Color Code			
Conductor(s)	PP - Polypropylene	0.009 in (0.23 mm) Bl	k, Red, White, Green			
Outer Shield							
Shield Type	Material	Cov	erage Dra	wire Type			
Tape	Bi-Laminate (Alum+F	oly) 100	% 24 A	G (7x32) TC			
Outer Jacket							
	ial Nam Th	ickness	Nom. Diar	eter Ripcord			
Mater	Nom. I						
	yl Chloride 0.017 in (0.188 in (4.7	mm) Yes			

Electrical Characteristics

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Max. Current
Conductor(s	6.5 Ohm/1000ft (21 Ohm/km)	27 pF/ft (89 pF/m)	48.5 pF/ft (159 pF/m)	4 Amps per conductor @ 25°C

Voltage

UL Voltage Rating 300 V (CMR)

Mechanical Characteristics

Temperature

UL Temperature	Operating		
75°C	-20°C to +75°C		

Bend Radius

Stationary Min.	Installation Min.		
1.9 in (48 mm)	1.9 in (48 mm)		

Max. Pull Tension:	104 lbs (47.2 kg)
Bulk Cable Weight:	31 lbs/1000ft (46 kg/km)

Standards and Compliance

Environmental Suitability:	Indoor - Riser, Indoor		
Flammability / Reaction to Fire:	UL1666 Riser, FT4, IEC 60332-1-2		
CPR Compliance:	CPR Euroclass: Eca		
NEC / UL Compliance:	Article 800, CMR		
CEC / C(UL) Compliance:	CMG		
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)		
APAC Compliance:	China RoHS II (GB/T 26572-2011)		
Plenum Number:	6302FE		

History

Update and Revision:

Revision Number: 0.266 Revision Date: 02-08-2022

Part Numbers

Variants

ltem #	Color	Putup Type	Length	UPC/EAN
5302FE.00152	Chrome	Reel	152 m	8719605008220
5302FE.00305	Chrome	Reel	305 m	8719605008237
5302FE.00U305	Chrome	Reel	305 m	8719605008244
5302FE 0081000	Gray			612825336846
5302FE 008500	Gray			612825159551
5302FE 008C250	Gray			
5302FE 008U1000	Gray			612825159537
5302FE 008U500	Gray			612825159544

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.