



**Product:** [37502](#)

Lead Wire, #2 Str TC, EPDM Ins, AWM 3499

[Request Sample](#)

**Product Description**

Rubber Lead Wire, 2AWG (163x24) Tinned Copper, EPDM Insulation, AWM 3499 7500V 150C

**Technical Specifications**

**Product Overview**

Suitable Applications:	internal wiring of appliances, high voltage and high temperature applications
------------------------	---

**Construction Details**

**Conductor**

Size	Stranding	Material
2	163x24	TC - Tinned Copper

**Insulation**

Material	Nom. Thickness	Nom. Insulation Diameter
EPDM - Ethylene Propylene Diene Monomer	0.131 in (3.33 mm)	0.581 in (14.8 mm)
Overall Cable Diameter (Nominal):	0.581 in (14.8 mm)	

**Electrical Characteristics**

**Electricals**

Nom. Conductor DCR	Max. Current
0.16 Ohm/1000ft (0.52 Ohm/km)	Single conductor in free air @ 30°C: 255 A

**Voltage**

UL Voltage Rating
7500 V RMS

**Mechanical Characteristics**

**Temperature**

UL Temperature	Operating
150°C	-55°C To +150°C
Recommended Max Baking Cycles:	24 Hours @ 300°F (149°C) ~ 4 Hours @ 375°F (190°C)
Bulk Cable Weight:	317 lbs/1000ft (472 kg/km)

**Standards and Compliance**

Sustainability:	CA Prop 65
AWM Compliance:	AWM 3499
European Directive Compliance:	EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

**Product Notes**

Notes:	Separartor Material over Conductor: Y
--------	---------------------------------------

## History

Update and Revision: Revision Number: 0.378 Revision Date: 12-15-2021

## Part Numbers

### Variants

Item #	Color	Putup Type	Length	UPC
37502 01050	Black	Reel	50 ft	612825147275
37502 010500	Black	Reel	500 ft	612825147282
37502 0101000	Black	Reel	1,000 ft	612825147268

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.